MINUTES OF THE MEETING OF CABINET COMMITTEE ON INFRASTRUCTURE (CCI) HELD ON 26th DECEMBER, 2018 IN THE CONFERENCE HALL OF HON'BLE CHIEF MINISTER

A meeting of the Cabinet Committee on Infrastructure (CCI)was held in the Conference Hall of the Hon'ble Chief Minister on 26thDecember, 2018to discuss various issues as per agenda circulated vide No.PD(SPD)-63/CCI/2015-16 (Part) dated 24/12/2018.

- 2. The meeting was chaired by Hon'ble Chief Minister and attended by Hon'ble Deputy Chief Minister, Chief Secretary, Commissioner (FPI), Secretary to CM, Special Secretary (Planning) and officials of Planning Department.
- 3. Concerned departments gave power point presentations on the respective proposals/issues for appraisal of the CCI. The proposals/issues were discussed in detail and after threadbare discussion, the following decisions were taken:-

I. Decisions on Policy related issues:-

Decision No-1:

It has been observed that a number of schemes relating to construction of boundary walls are being implemented and also being proposed to be implemented in the State under various schemes/programmes. It was noted that there was no standard design and specification for such walls around Govt. buildings (both residential and Non-residential), schools, health centres etc. It was also observed that there was no uniformity in preparing the estimates, design & specification of the boundary wall and hence the cost estimates submitted by various executing departments varied to a large extant. It was, therefore, decided to streamline construction of such boundary walls adopting a uniform and standard drawing, design & specification and costing throughout the State. It was finally resolved that henceforth, all departments / executing agencies shall follow the standard drawing and costing as per the Office Memorandum issued by the Finance, Planning & Investment department (Annexure-I).

Decision No-2:

It has also been observed that various types of Govt. buildings are constructed in the State under various schemes/programmes by rates/estimates. adopting different departments Departments tend to prepare estimates of single/double/triple incorporating higher sides buildings on specifications which may be functionally not required. It was also noted that there is no standard design and specification for construction of Govt. buildings (both residential and Nonresidential). This leads to artificial inflation and accordingly nonuniformity in the cost of the projects pertaining to construction of such buildings by various departments. It was, therefore, decided to streamline the preparation of estimates of various categories of buildings throughout the State by adopting a uniform design, specification and standard costing based on CPWD Plinth Area

DOW)



Rate 2012. It was decided that henceforth, all departments / executing agencies shall follow the standard drawing and costing as per the Office Memorandum issued by the Finance, Planning & Investment Department (Annexure-II).

Decision No-3:

It has been observed that only about one third of the roads in the are complete Cement Concrete/Bituminous Formation cutting of roads is taken up every year by various executing departments under different schemes without any provision for proper drainage, culverts and black topping. Since formation cutting is not a permanent kind of structure, there is frequent damage to these roads during rainy seasons due to landslides/mudslides thereby causing huge loss to public exchequer. It was felt that there is an urgent need to check this trend and invest the scarce public resources in the road sector in a planned manner so as to ensure optimum utilisation of fund. The Proposal put forward by the PWD in this regard was approved in principle by the CCI. It was decided that henceforth, priority will be given to provide connectivity to the unconnected administrative centres and surfacing / resurfacing of major district roads and township roads. Accordingly it was decided that a two phased strategy shall be adopted for providing better road connectivity in the State which is as follows:

1) PWD will identify strategic roads required for connecting unconnected district headquarters, and sub divisional headquarters and also prepare a plan for re-surfacing of roads connecting such administrative centres in a phased manner depending upon the availability of funds.

2) PWD will identify strategic roads required for connecting unconnected EAC/CO headquarters, prepare a comprehensive plan for connecting such administrative centres and also prepare a re-surfacing plan of roads connecting such administrative centres in each district in a phased manner depending upon the availability of funds.

Detailed Action Plan in this regard will be submitted by the PWD within one month time and the same will be accordingly included in the Budget after due examination and prioritisation. Every year sufficient fund will be earmarked for connecting the unconnected administrative centres and accordingly resurfacing of such important roads will be carried out from the State Budget and other sources from Government of India.

Decision No-4:

It was brought to the notice that that there is an urgent need to connect the Itanagar-Jote Road to two-lane Highway in view of the huge economic potential of the area and also to provide better connectivity to important State Level institutes like the Film and Television Institute (FTI), National Institute of Technology

ADD



(NIT), Law College etc. which have been established in and around Jote. It was decided that the proposal will be submitted to the MoRTH, Government of India for consideration under CRF as "Road of Economic Importance".

Decision No-5:

It was brought to the notice of the CCI that as per the guidelines of PMGSY, 10% of allocation is to be provided by the State Govt. for routine maintenance of PMGSY roads. It was informed by the Rural Works Department that if the same is not provided by the State Govt there is a possibility of reduction in the allocation of fund under PMGSY by the Govt. of India. It was further apprised by Planning Department thatalthough the Rural Works Department has been approaching the Finance, Planning & Investment Department for providing additional fund for routine and emergency maintenance of PMGSY roads but the same was not allocated since RWD was yet to submit the report of the Committee for Resource Mobilization and also the Norms for Maintenance of Rural Roads as envisaged in the Arunachal Pradesh Rural Roads Maintenance Policy- 2017 notified by the State Government vide Memo No.SRWD-43/PMGSY/2016-17 dated 31st December, 2017. However, considering the request of the department for allocation of fund for urgent repair and maintenance of the PMGSY roads in public interest, as per the aforesaid policy and norms prescribed by Ministry of Rural Development, Government of India, onetime allocation of Rs. 18.97 Crore under SIDF during 2018-19 was approved by the CCI to meet the commitment under PMGSY. Further. maintenance of such PMGSY roads will be supervised by the concerned Deputy Commissioners and accordingly Geo-Tagged photographs and a certificate duly signed by the Chief Engineer. Superintendent Engineer & Executive Engineer countersigned by Deputy Commissioner will be submitted to the planning department. It was decided that the Department should comply with the provisions of the Arunachal Pradesh Rural Roads Maintenance Policy - 2017 and accordingly submit requisite proposal for keeping necessary fund provision in the next Budget.

Decision No-6:

The CCI directed the RWD to conduct soil testing for the Miao-Vijaynagar road in consultation with the Chief Engineer (D&P), PWD and find a technical solution for construction of the stretch which falls under marshy land to facilitate early completion of the project. Further, the department was asked to submit the estimates pertaining to the damages caused by flood and slides during 2017 to the Planning Department for considering the proposal for funding by the Ministry of DoNER.

Decision No-7:

It was also decided that all works should be executed by the concerned implementing departments as per allocation of Business Rules. Accordingly, it was decided that the work pertaining to "C/o Gym and Officers Club in Banquet Hall"



approved under SIDF and earlier allotted to UD & Housing Department shall be implemented by PWD.

II. Decisions on project proposals:-

| SI. | | |
|-----|---|---|
| No | Department/Projects | Decisions/Remarks |
| 1 | 2 | 3 |
| 1 | PWD | |
| 1 | C/o residential buildings for the Chairperson and Members of State Human Rights Commission | The matter should be pursued constantly by the Home Department in consultation with SHRC and PWD being the executing department. Possibility of constructing Lokayukta Building in the same complex shall also be explored |
| 2 | C/o boundary wall for newly allotted plots at Dheerpur and Dwarka in New Delhi | The proposal is approved in principle for an amount of Rs.1.77 Crore. However, an amount of Rs.50 lakhs is allocated for starting the project during CFY. |
| 3 | C/o bridge over river Papum in between Langdung and Byate village at chainage 12.060 km | It was informed by the department that the project is under Arbitration. It was observed that due to laxity and negligence of the executing departments, the arbitration matters are not being contested and defended properly in the interest of the Government. It was decided that all the arbitration matters should be brought to the notice of the HCM/HDCM along with present status through the Chief Secretary by the concerned Principle Secretary/Commissioner/Secretary. Any decision on allocation of fund shall be made only after settlement of the case. Department should submit the estimated of the project to the Committee of Engineers constituted by the CCI for examination and |
| 4 | C/o Arunachal Arogya Bhawan at Shillong | verification of the cost escalation. The Health & Family Welfare Department should immediately hand over the ownership of land both at Shillong and Vellore where such facilities are coming up for the patients to the General Administration Department for construction of the aforesaid project and also for their maintenance in future. The project is approved in principle for an estimated cost of Rs. 26.00 Crore and the department shall get the estimates vetted by the CE (D&P), PWD. Allocation of Rs. 2.60 Crore during CFY under SIDF was approved. |

| | 14 | | |
|---|-----|--|---|
| 8 | 6 | Construction of District Secretariat Buildings at Khonsa, Namsai and Tezu | Allocation during CFY i.e. Rs 2.00 Crore for Tezu, Rs 4.00 Crore for Namsai and Rs. 7.50 Crore for Khonsa under SIDF was approved. Department was asked to expedite completion of the projects. Commissioner PWD and respective Deputy Commissioners should personally monitor & follow up the construction of these projects. Deputy Commissioners should also include the status of construction of these projects in their monthly confidential reports. |
| | 7 | C/o Residential building for HCM at Niti Vihar, Itanagar | The proposal was approved in principle. An Allocation of Rs. 2.00 Crore under SIDF was approved to start the construction of the residential building during CFY. |
| | 8 | Major renovation and refurbishing of the first floor of Golden Jubilee Banquet Hall at Itanagar (Additional agenda Item). | The project was approved in principle for an amount of Rs 1.50 Crore subject to vetting of estimate by the CE (D&P). Department should keep necessary provision in the estimates for providing latest acoustic facilities, LED screen, standard furniture etc. in consultation with Department of IPR and Power. Rs. 50 lakh was earmarked during the CFY. |
| | 9 | C/o Boundary wall and gate around R.K. Mission School at Narottamnagar (Additional agenda Item). | The project was approved for an amount of Rs 2.85 Crore. An Allocation of Rs. 30 lakhs under SIDF during CFY was approved, Department shall propose the provision of balance amount in next year's SADA. |
| | - | PHE & WS | |
| | 1 | Augmentation of Water Supply to Rajiv Gandhi University Campus Rono Hills (through lift), Doimukh. | The project was approved in principle. Cost of the project should be restricted within Rs. 20.00 Crore as per the Budget Announcement. Department should immediately start implementation of the project and complete the same in a time bound manner so as to mitigate the problem of drinking water in the RGU campus. |
| 2 | 2 | Water conservation measure in the catchment area of Longding drinking water source and to rectify the damages caused to the formation works. | The project was approved in principle. Allocation of Rs 2.00 Crore was approved under SIDF during CFY. The project shall be implemented under the supervision of the Deputy Commissioner, Longding. |
| - | 111 | UD & Housing | |
| | 1 | Additional item of works for | It was decided that the DPR pertaining to |
| _ | | | |

CON

| paring | | 6 |
|------------------|---|---|
| an orași O ar | "C/o MLA Apartment at Chimpu, Itanagar" | escalation of cost be vetted by the Cl (D&P), PWD. No contingency charge should be included. It was further decide that the NDRF personnel temporaril camping in one of the blocks of ML/apartment (which is to be furnished) shoul be immediately shifted to alternative site a proposed by the Department of UD and Housing to facilitate completion of balance work expeditiously. Deputy Commissionel ICC shall issue necessary orders in this regard and ensure shifting of NDRI personnel accordingly. Department should complete all pending works pertaining the MLA Apartments by March, 2019. After detailed deliberation, it was decided that a uniform provision should be prescribed for furnishing the apartments. Keeping in view the scarcity of state's resources, it was decided unanimously that the upper limit of furnishing the Bunglow of Hon'ble Speaker shall be Rs. 20 lacs, Hon'ble Deputy Speaker shall be Rs. 15 lacs and Rs 10 lakh for each MLA. |
| 2 | Pending liabilities under CSS (JnNURM) (Sector roads) | An allocation of Rs 3.01 Crore was approved under SIDF during CFY after going through the recommendation of the Technical Committee. |
| 3 | Additional works at D.K. Convention Hall, Itanagar | The proposal needs to be vetted by the Committee of Chief Engineers constituted by the CCI. No contingency charges shall be permitted. |
| 4 | C/o Outdoor stadium at Ziro (additional items) | Proposal for additional allocation was no considered by the CCI. It was decided that the department will complete the parking area within the sanctioned amount. |
| 5 | Revised estimate of C/o Dorjee Khandu Memorial Badminton Academy at Itanagar including approach road and bridge | CCI noted that the project has been abnormally delayed by the UD and Sports Department. It was decided that the total cost of the project viz. C/o Dorjee Khandu Memorial Badminton Academy at Itanagar should be restricted within Rs. 35.61 crores as approved earlier and the DPR accordingly be framed in consultation with the Sports Department. It should be ensured that all state of the art facilities are incorporated in the DPR. Secretary UD and Secretary Sports and Youth Affairs to prepare a comprehensive DPR within 1 months time. |

| ()3 | | |
|------|---|--|
| IV | Hydro Power | |
| 1 | Renovation & modernization work of Sessa MHS (3x 500 kW) | The project was approved in principle subject to the condition that the DPR should be vetted by the competent authority of Alternate Hydro Energy Centre (AHEC), IIT, Roorkie. No contingency charges shall be allowed. Rs. 1.00 Crore under SIDF was allocated during CFY. Balance fund is to be kept by the department in next year's SADA. |
| 2 | (2x 50 kW) | The justification/reasons submitted by the department for the special repair were not convincing and therefore were not accepted by the Committee. Department was advised to undertake techno-economic feasibility study of the project by Alternate Hydro Energy Centre (AHEC), IIT, Roorkie |
| 3 | Revision of project Implementation of Pagu MHS (2x1000 KW) at Choba | The justification/reasons submitted by the department for the special repair were not convincing and therefore were not accepted by the Committee. Department was advised to undertake techno-economic feasibility study of the project by Alternate Hydro Energy Centre (AHEC), IIT, Roorkie |
| 4 | Special repair & maintenance of damage in Unit - III of Nuranang SHP Phase-I (3X 1000 KW) at Tawang | After detailed deliberation, it was decided to allocate Rs. 1 Crores under SIDF during CFY for the repair and maintenance of the project. |
| 5 | Special repair of (2X 500 KW) Domkhrong Hydro Power Project at Kalaktang | After detailed deliberation, it was decided to allocate Rs. 87 Lacs under SIDF during CFY for the repair and maintenance of the project. |
| V | Law & Judicial | |
| 1 | Infrastructure for Judiciary | CCI appreciated the fact that State requires funds for construction of requisite judicial infrastructure facilities in several districts in the state. Government of India has assured to provide Rs. 10 Crore for this purpose. It was also informed that the said amount of Rs. 10 Crores shall be released by Government of India only on submission of pending utilisation certificates. The executing departments were directed to submit the UCs urgently to Govt of India so that the allocated amount of Rs. 10 Crores is released expeditiously. It was also directed that since Hon'ble Supreme Court and Hon'ble High court were monitoring the construction of Court Buildings and other infrastructure facilities, the construction |

(N)

| 50 SV | | 8 |
|--------|--|---|
| | | |
| agar L | | work shall be expedited by the executing agencies and the current status be submitted in this regard every month by the respective DCs and Commissioner (Law) in their monthly report. It was also decided to keep a provision of Rs. 5 Crores during this financial year for this purpose keeping in view the importance and urgency of providing requisite judicial infrastructure facilities in the state. Thus, in all a provision of Rs 15 Crores (Rs. 10 Crores from Government of India + Rs. 5 Crores from State's Budget) was approved by the Committee during CFY. In addition, it was decided that a provision of Rs. 1 Crores be kept for repair and maintenance of Judicial Infrastructure during CFY. It was also noted that uniformity in design, specification as prescribed by Hon'ble High Court and cost estimates be maintained in construction of all court buildings. It was also observed that the cost estimates were on the higher side and therefore it was decided that the cost estimates of all the Court Buildings be got vetted/verified by Chief Engineer (D&P), PWD. |
| VII | Animal Hughandry & D/Doy | |
| 1 | Animal Husbandry & D/Dev. Establishment of State of Art Dairy Farm at Bomjir in Lower Dibang Valley | CCI was of the view that the project should be implemented in consultation with NDDB after ascertaining the economic feasibility and viability of the project. The department was directed to also specify all administrative arrangements necessary for successful and viable operation of state of the art Dairy Farm. Department was advised to re-work the entire proposal accordingly. |
| VIII | Science & Technology | |
| 1 | Planet lab subscription for daily monitoring | The Department was directed to immediately submit the proposal for subscription of maps of 3.00 metre resolution to Planning Department for onward submission of the same to the North Eastern Council for funding. |

4. All proposals received for consideration under SIDF during 2018-19 was placed before the CCI which in principle approved 1608 numbers of schemes which shall be notified by Planning Department separately after proper scrutiny.

It was reiterated that the following conditions should be followed and adhered to by all the executing Departments without fail:-

- i. This allocation is purely indicative in nature and this shall be utilized by the department only after verifying the actual requirement and observance of guidelines and all the financial rules, regulation, provisions prescribed in GFR, DFPR etc. & guidelines/ circulars/ OM's/directives issued by the CVC, MoF, MAH, GoI, Administrative Ministries of GoI & GoAP from time to time in this regard in letter & spirit without fail.
- ii. The department shall complete the projects within the estimated cost approved by the CCI and no additional fund shall be allocated for this purpose in future.
- iii. The concerned Commissioner/ Secretary shall monitor and review the progress of implementation of aforesaid schemes/ projects at regular intervals and shall ensure timely submission of progress report, utilization certificate, photographs and completion certificate etc. as applicable only after necessary review/ verification at their level.
- iv. Violation of above instruction/guidelines will be the sole responsibility of the officers concerned.
- 6. The meeting then ended with vote of thanks form the Special Secretary (Planning).
- 7. This is issued with the approval of Hon'ble Chief Minister.

Sd/-(Satya Gopal) IAS Chief Secretary

Memo No. PD (SPD) -63/2015-16(Part) Copy to: Dated, the 11th January, 2019.

- 1. The Secretary to Hon'ble Chief Minister, Govt. of Arunachal Pradesh, Itanagar.
- 2. PPS to Hon'ble Chief Minister, Govt. of Arunachal Pradesh, Itanagar.
- 3. PS to Hon'ble Deputy Chief Minister, Govt. of Arunachal Pradesh, Itanagar.
- 4. US to Chief Secretary, Govt. of Arunachal Pradesh, Itanagar.
- 5. All Commissioners / Secretaries, Govt. of Arunachal Pradesh, Itanagar.
- 6. The Joint Secretary (Cabinet), Govt. of Arunachal Pradesh, Itanagar.
- 7. All Chief Engineers and Directors, Govt. of Arunachal Pradesh, Itanagar.
- 8. All Deputy Commissioners, Govt. of Arunachal Pradesh, Itanagar.
- 9. PA to Secretary (Planning), Govt. of Arunachal Pradesh, Itanagar.

(Himanshu Gupta), IAS Special Secretary (Planning & Investment)



GOVERNMENT OF ARUNACHAL PRADESH FINANCE, PLANNING & INVESTMENT DEPARTMENT BLOCK No. 1,4TH FLOOR:

CIVIL SECRETARIAT:: ITANAGAR

OFFICE MEMORANDUM

No. PD(SPD)-63/CCI/2015-16

Dated, Itanagar the 15th January 2019

It has been observed that there is no uniformity and standardisation of construction of boundary walls by various departments. Hence, in order to ensure uniformity and standardisation of construction of boundary wall of both residential and non-residential buildings implemented by various departments of State Government, Cabinet Committee on Infrastructure has approved the following:

- 1. The drawings and the cost of boundary wall per metre run which has been prepared at par APSR-2018(Buildings) shall be used uniformly in the state. For estimation purpose, this rate shall be used for two years, i.e. until 2020. The boundary wall of CC/brick wall with decorative grill on the top of wall shall be adopted for important non-residential buildings as attached in the Annexure-A & A1.
- 2. The boundary wall of CC/brick wall with CC coping at the top of wall shall be adopted for normal non-residential building and residential building of Type-V and above as attached in Annexure-B & B1.
- 3. The boundary wall with CC/brick wall up to a height of 0.60m with chain link fencing above shall be adopted for residential building of Type-I to Type-IV and PHCs, CHCs and schools upto secondary level as attached in Annexure-C & C1.

The cost of boundary wall constructed in various locations involving higher carriage of materials shall be analysed based on the APSR-2018 (Buildings) adopting the same drawing. Furthermore, this rate shall not be adopted directly for payment to contractor since payment for work done shall be based on the rate in tender agreement. The cost of the wall shall be updated with the release of updated APSR (Buildings) by Public Works Department of Arunachal Pradesh.

The estimation for boundary wall to be constructed outside the State shall be done using the same drawings with schedule of rates prevailing in that particular State/Union Territories.

While according Administrative approval and Expenditure Sanction, it shall be the duty of Concerned Secretary/Commissioner that the aforesaid guidelines are followed in letter and spirit.

(Kaling Tayeng), IAS
Development Commissioner (FP&I)
Govt. of AP., Itanagar

Memo No. PD(SPD)-63/CCI/2015-16 Copy to: Dated, Itanagar the 15th January 2019

- 1. The Commissioner to Hon'ble Governor, Arunachal Pradesh, Itanagar.
- 2. The Secretary to HCM, Arunachal Pradesh, Itanagar.
- 3. PS to HDCM, Aruanachal Pradesh, Itanagar.
- 4. PS to Cabinet Ministers, Government of Arunachal Pradesh
- 5. Under Secretary to Chief Secretary, Govt. of A.P, Itanagar.
- 6. All Commissioners/Secretaries/Special Secretaries, Arunachal Pradesh
- 7. All Chief Engineers/Directors/Superintend Engineers/Executive Engineers of all Zones, Arunachal Pradesh
- 8. Secretary Finance for information and necessary action please

(Himanshu Gupta), IAS Special Secretary (Planning & Investment)

Govt of A.P, Itanagar

Division:-Sub-Division:-

ABSTRACT OF COST-ORIGINAL ESTIMATE

State :- A.P.

Branch:- B&R

Name of Work: - C/o Boundary wall with Grill for Important Non-Residential Buildings.

| Lane | The same of the sa | | | | | to brief an _{co} ntemperations describe an expension participant and on the contemperature of the contemperature of | |
|--------------------|--|--|-------|---------|------|--|---------------|
| N. P. COLUMNIC CO. | SI. No. | Sub-Head and Items of work | Qty | Rate | Unit | Amount | Remarks |
| | 1 | 2 | 3 | 4 | 5 | 9 | 7 |
| <u> </u> | - | Earth work in excavation in foundation and trenches in soils containing 50% or more of shingle or small size boulders upto 30 cm size, lift upto 1.50 m and stacking the excavated soil not more than 3 m clear from the edge of the excavation and returning the stacked soil in 15 cm layers when required, into plinth, sides of foundation etc consolidating each deposited layer by ramming and watering and then disposing of all surplus excavated soil as directed within a lead of 50m. | 19.09 | 281,30 | Cum | 5368.61 | SH: EW, I-4 |
| | 2 | Providing and laying in foundations and plinth cement concrete 1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. | 2.05 | 4754.90 | Cum | 9733.28 | SH: CC, 1-2 |
| | 3 | Providing and laying in foundations and plinth cement concrete 1:3:6 (1 cement: 3 coarse sand: 6 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. A) Foundation and plinth. | 1.86 | 5323.20 | Cum | 9917.12 | SH: CC, 1-4 |
| | 4 | Reinforced concrete work in foundations, footings, bases of columns etc. and mass concrete excluding cost of centring, shuttering and reinforcement in : a) M20 (1 cement : 1.5 coarse sand : 3 stone aggregate 20 mm nominal size) | 1.17 | 7801.90 | Cum | 9128.22 | SH: RCC, 1-1 |
| | rv | Reinforcement cement concrete work in columns, pillars, piers, abutments, post and struts etc upto floor two level including finishing and plastering the exposed surface with cement mortar 1:3 (1 cement:3 fine sand) of thickness not exceeding 6 mm to give a smooth and even surface but exluding cost of centring, shuttering and reinforcement. a) M20 (1 cement: 1.5 coarse sand: 3 stone aggregate 20 mm nominal size) | 2.17 | 9013.10 | Cum | 19524,67 | SH: RCC, 1-7 |
| - | 9 | Reinforced cement concrete work in lintels, beams and bresumers up to floor two level including finishing and plastering the exposed surface with cement mortar1.3 (1cement.3finesand) of thickness not exceeding 6mm to give a smooth and even surface but excluding cost of centering, shuttering and reinforcement. a) M20 (1 cement : 1.5 coarse sand : 3 stone aggregate 20 mm nominal size). | 2.54 | 8915.10 | Cum | 22626.52 | SH: RCC, 1-6 |
| | 7 | Centring and shuttering including strutting, propping etc and removal of form work for | | | | | |
| | | a) Foundation, footings, bases of columns etc. and mass concrete | 11.96 | 348.10 | Sqm | 4163.28 | SH: RCC, 1-12 |
| | | b) Lintels, beams, girders, bressumers and cantilevers etc. | 20.25 | 458.60 | Sqm | 9286.65 | SH: RCC, 1-12 |

| No. | Sub-Head and Items of work | Oty | Rate | Unit | Amount | Remarks |
|-----|--|--------|---------|-------|--------------|-----------------|
| 1 | 2 | 3 | 4 | S | 9 | 7 |
| | c) Column, pillars, posts and struts etc. | 37.67 | 584.60 | Sqm | 22024.22 | SH: RCC, 1-12 |
| ∞ | Reinforcement of RCC work including bending, binding and placing in position complete. b) Tor/TMT steel. | 553.45 | 88.60 | Kg | 49035.52 | SH: RCC, 1-19 |
| 6 | Half brick masonry (with best available local bricks) in cement mortar 1:4 (1 cement : 4 fine sand) in foundations and plinth. | 37.80 | 00'886 | Cum | 37346.40 | SH: BW, I-12 |
| 10 | Extra for half brick work with best available local bricks in superstructure above plinth level up to floor two level. | 37.80 | 39.10 | Cum | 1477.98 | SH: BW, I-13 |
| 11 | Providing and fixing MS grills of required pattern in wooden frames of windows etc with MS flat, square or round bars with round headed bolts and nuts or by screws. | 274.31 | 135.20 | Kg | 37087.33 | SH: WW, I-22 |
| 12 | 12 mm cement plaster $1:4$ (1 cement : 4 fine sand). | 75.60 | 167.50 | Sqm | 12663.00 | SH: Fin, 1-2 |
| 13 | Colour washing such as green, blue or buff on new work (two or more coats) including a base coat of white washing with lime to give an even shade | 108.00 | 21.70 | Sqm | 2343.60 | SH: Fin, 1-42 |
| | Sub-Total (A) | | | | ₹ 251,726.41 | |
| | CARRIAGE OF MATERIAL | | | | | |
| 14 | Loading and Unloading of Stone Boulder/ Stone aggregates / Sand / Kanker Moorum/ Lime / Shingle/Surki / Earth/ Excavated Rock and Kerb Stones by Manual Means for hill roads | 26.72 | 214.00 | Cum | ₹ 5,718.20 | SH: Carr, 1-1.6 |
| 15 | Loading and Unloading of Cement/ Steel / Structural Steel/RC Pipe/ Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hill roads. | 7.00 | 264.00 | MT | ₹ 1,847.30 | SH: Carr, 1-1.6 |
| 16 | Cost of Haulage excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | | | |
| a) | Surfaced Road | | | | | |
| | Cement/Steel [From Guwahaty to Itanagar 410 km] [Rate = $410 \times 10.5 = Rs. 4305.00$] | 7.00 | 4305.00 | MT/Km | ₹ 30,123.53 | SH: Carr, 1-1.8 |
| | Bricks [From Bishwanath Chariali to Itanagar 105 km] [Rate = $105 \times 10.5 = Rs. 1102.50$] | 7.27 | 1102.50 | MT/km | ₹ 8,014.33 | SH: Carr, I-1.8 |
| | Sand/Agg [25 km] [Rate = $25 \times 10.5 = Rs. 262.50$] | 26.72 | 262.50 | MT/km | ₹7,014.15 | SH: Carr, 1-1.8 |
| (q | Unsurfaced Graveled Road | | | | | |
| | Sand / Agg [5 km] [Rate = $5 \times 12.60 = Rs. 63.00$] | 26.72 | 63.00 | MT/km | ₹ 1,683.40 | SH: Carr, 1-1.8 |

 $\mathcal{H}^{'''}$

| AND DESCRIPTION OF THE PERSON NAMED IN | | equence and an analysis of the second | A ADMINISTRATION OF ANY ADMINISTRATION OF A STREET, STATEMENT OF A S | Contract and the contract from | Committed by pare \$200 materials for \$50 bissing both the committee of the Children of the Chi | Control and communications of the Control and Control |
|--|---|---------------------------------------|--|--|--|---|
| SI. No. | Sub-Head and Items of work | Qty | Rate | Unit | Amount | Remarks |
| 1 | 2 | 3 | 4 | 5 | 9 | 7 |
| c) | c) Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. [2km] [Rate = $2 \times 25.40 = Rs. 50.80$] | 26.72 | 50.80 | MT/km | ₹ 1,357.41 | SH: Carr, 1-1.8 |
| | Sub-Total (B) | | | | ₹ 55,758.31 | |
| | Cost: | or 30.00 m | Cost for $30.00 \text{ m} = [A+B] =$ | | ₹ 307,484.72 | |

Cost for 30.00 m = [A+B] =

Cost per Mtr =

₹ 10,250.00

Details of Measurement

Name of Work:- C/o Boundary wall with Grill for Important Non-Residential Buildings.

[Calculation for Wall length of 30.00 Mtrs]

| tem No. | Description of Item | No. | Length | Breadth | Height | Quantity |
|------------|---|-----|--------|---------|-----------|---------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 1 | Earth work in excavation in foundation and trenches | | | | | - |
| | Columns | 13 | 1.00 | 1.00 | 1.25 | 16.25 Cum |
| | Walls | 12 | 1.50 | 0.45 | 0.35 | 2.84 Cum |
| | Total | | | | | 19.09 Cum |
| 2 | Providing and laying PCC 1:4:8 in foundation | | | | | |
| | Columns | 13 | 0.80 | 0.80 | 0.10 | 0.83 Cum |
| | Walls | 12 | 2.25 | 0.45 | 0.10 | 1.22 Cum |
| | Total | | | | | 2.05 Cum |
| 3 | Providing and laying PCC 1:3:6 in foundation | | | | | |
| | Below plinth beam | 12 | 2.25 | 0.23 | 0.30 | 1.86 Cum |
| | Total | : | | | | 1.86 Cum |
| 4 | RCC Work in Foundation footings. | 13 | 0.60 | 0.60 | 0.25 | 1.17 Cum |
| | Total | | | | | 1.17 Cum |
| 5 | RCC Work in Columns | 13 | 0.23 | 0.23 | 3.15 | 2.17 Cum |
| | Total | | | | | 2.17 Cum |
| 6 | RCC work in Beams | 12 | 2.25 | 0.23 | 0.30 | 1.86 Cum |
| | Coping | 12 | 2.25 | 0.25 | 0.10 | 0.68 Cum |
| | Total | | | | | 2.54 Cum |
| 7 | Centering and shuttering | | | | | |
| a) | Foundation, footings, | 13 | 3.20 | | 0.10 | 4.16 Sqm |
| | | 13 | 2.40 | | 0.25 | 7.80 Sqm |
| b) | Total Beams | 12 | 2.25 | | 0.20 | 11.96 Sqm 5.40 Sqm |
| 0) | Deanis | 12 | 2.25 | | 0.55 | 14.85 Sqm |
| | Total | 12 | 2.23 | | 0.55 | 20.25 Sqn |
| c) | Column | 13 | 3.15 | | 0.92 | 37.67 Sqm |
| | Total | | | | | 37.67 Sqm |
| 8 | Reinforcement for RCC | | | | | |
| | Column Footing 10mm dia bars 5 Nos both ways | 130 | 0.60 | @ | 0.62 kg/m | 48.36 Kg |
| | Col Main bars 12mm dia 4 Nos | 52 | 3.55 | @ | 0.89 kg/m | 164.29 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 208 | 0.85 | @ | 0.39 kg/m | 68.95 Kg |
| | Beam reinforcement 12mm dia 4 Nos | 4 | 30.60 | · @ | 0.89 kg/m | 108.94 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 180 | 0.85 | @ | 0.39 kg/m | 59.67 Kg |
| | Coping bar 10mm dia 2 Nos | 2 | 30.60 | @ | 0.62 kg/m | 37.94 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 208 | 0.48 | @ | 0.39 kg/m | 38.94 Kg |

| | | | | | 527.09 Kg |
|---|---|--|--|--|---|
| Add 5% for Wastage and overlapping | | | | | 26.35 Kg |
| | | | | Total = | 553.45 Kg |
| Half Brick work in cement mortar 1:4 | 12 | 2.25 | 1.40 | | 37.80 Sqm |
| Extra for Brick work in Super structure | | | | | 37.80 Sqm |
| MS Grill | | | | | |
| MS Flat 40 x 5 mm | 12 | 2.35 | a | 1.60 kg/m | 45.12 Kg |
| MS square bar 12 mm with arrow tips | 240 | 0.5 | @ | 1.13 kg/m | 135.60 Kg |
| Horizontal tie bar 12 mm | 24 | 2.35 | @ | 1.13 kg/m | 63.73 Kg |
| Hold Fast Angle iron 40x40x6mm | 24 | 0.2 | @ | 3.50 kg/m | 16.80 Kg |
| | | | | | 261.25 Kg |
| Add 5% for Wastage | | | | Total = | 13.06 Kg |
| To | otal | | | | 274.31 Kg |
| 12mm Cement Plaster 1:4 CM | 24 | 2.25 | | 1.40 | 75.60 Sqm |
| Colour washing | 2 | 30.00 | | 1.80 | 108.00 Sqm |
| | Half Brick work in cement mortar 1:4 Extra for Brick work in Super structure MS Grill MS Flat 40 x 5 mm MS square bar 12 mm with arrow tips Horizontal tie bar 12 mm Hold Fast Angle iron 40x40x6mm Add 5% for Wastage To | Half Brick work in cement mortar 1:4 Extra for Brick work in Super structure MS Grill MS Flat 40 x 5 mm 12 MS square bar 12 mm with arrow tips Horizontal tie bar 12 mm 24 Hold Fast Angle iron 40x40x6mm 24 Add 5% for Wastage Total 12mm Cement Plaster 1:4 CM 24 | Half Brick work in cement mortar 1:4 Extra for Brick work in Super structure MS Grill MS Flat 40 x 5 mm 12 2.35 MS square bar 12 mm with arrow tips Horizontal tie bar 12 mm 24 2.35 Hold Fast Angle iron 40x40x6mm 24 Add 5% for Wastage Total 12mm Cement Plaster 1:4 CM 24 2.25 | Half Brick work in cement mortar 1:4 Extra for Brick work in Super structure MS Grill MS Flat 40 x 5 mm 12 2.35 MS square bar 12 mm with arrow tips Horizontal tie bar 12 mm 24 2.35 Hold Fast Angle iron 40x40x6mm Add 5% for Wastage Total 12mm Cement Plaster 1:4 CM 24 2.25 | Total = Half Brick work in cement mortar 1:4 12 2.25 1.40 |

CARRIAGE OF MATERIAL


| 14 | Loading and Unloading of Stone Boulder I Stone aggregates / Sand I Kankerl Moorum/ Lime / Shingle ISurkii EarthI Excavated Rock and Kerb Stones by Manual Means forhillroads | | | 26.72 |
|----|--|--|--|-------|
| 15 | Loading and Unloading of Cement /Steel / Structural Steel / RC Pipe / Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hill roads. | | | 7.00 |
| 16 | Cost of Haulage Excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | |
| a) | Surfaced Road | | | |
| | Cement/Steel | | | 7.00 |
| | Bricks | | | 7.27 |
| | Sand/Agg | | | 26.72 |
| b) | Unsurfaced Graveled Road | | | |
| | Sand / Agg | | | 26.72 |
| c) | Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. | | | 26.72 |

TC STATEMENT

Name of work: C/o Boundary wall with Grill for Important Non-Residential Buildings.

| Z. | Irem of Works | Qty of Work | Unit | Cement | ent | Sa | Sand | Aggre | Aggregate | Bı | Bricks |
|----------------------------|-------------------------------|--|--|---|--|--|--|---|--|--------|----------|
| | | done | | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty |
| 1 | PCC 1:4:8 | 2.05 | Cum | 0.17 | 0.35 | 0.47 | 96.0 | 0.89 | 1.82 | | |
| 2 | PCC 1:3:6 | 1.86 | Cum | 0.22 | 0.41 | 0.47 | 0.88 | 0.89 | 1.66 | | |
| 3 | RCC in Foundation (M20) | 1.17 | Cum | 0.4 | 0.47 | 0.43 | 0.50 | 0.85 | 0.99 | | |
| 4 | RCC in Column (M20) | 2.17 | Cum | 0.4 | 0.87 | 0.43 | 0.93 | 0.85 | 1.84 | | |
| 52 | RCC in Beams (M20) | 2.54 | Cum | 0.42 | 1.07 | 0.47 | 1.19 | 0.85 | 2.16 | | |
| 9 | Half brick masonry in 1:4 CM | 37.80 | Cum | 0.078 | 2.95 | 0.267 | 1.01 | | | 50 | 1890 |
| _ | 12mm Cement Plaster in 1:5 CM | 75.60 | Sqm | 0,0446 | 0.34 | 0.154 | 1.16 | | | | |
| 80 | Reinforcement for RCC | 553,45 | Kg | | | | | | | | |
| | | | | | 6.44 MT | | 6.64 Cum | | 8.47 Cum | | 1890 Nos |
| ACMITTACAZACIO GATE WATER. | | 40 Вестроння применент при | STATES AND SECURITY AND ADDRESS OF THE PARTY | COMMING CONTINUES TO CALCESTO CONTINUES ACTION OF THE CONTINUES OF T | Apparent of the contract of th | CONTRACTOR OF THE PERSON OF TH | BARROOM SECONDALISM SECONDALISM SPECIAL SPECIA | CONTRACTOR DESCRIPTION OF THE PROPERTY OF THE | Control of the Contro | | |

| | 6.44 MT | 0.55 MT | 7.00 MT | 10.62 MT | 16.10 MT | 26.72 MT | 7.27 MT |
|------------------------|---------|---------|---------|----------|-----------|-----------|---------|
| | | | | 6.64 Cum | | 15.11 Cum | |
| | Cement | Steel | | Sand | Aggregate | | Bricks |
| Carriage of Materials: | | | | | | | |



ABSTRACT OF COST-ORIGINAL ESTIMATE

State :- A.P. Branch:- B&R

Division:-Sub-Division :-

Name of Work:- C/o Boundary wall with Coping for Normal Non-Residential and Residential (Type-V and above Type) Buildings.

| Z | ame | Name of Work : Co Boundary wan with Coping to the contract of the contract of the coping of the copi | | | William Control of the Control of th | SAN FOLLOWS COMMISSION STOCKED STOCKED CONTRACTOR OF THE STOCKED CONTR | выполнительности на применения пр |
|-------------------|-----|--|-------|---------|--|--|--|
| Sl. No. | No. | Sub-Head and Items of work | Otty | Rate | Unit | Amount | Remarks |
| - | 1 | | 3 | 4 | 2 | 9 | 7 |
| | | Earth work in excavation in foundation and trenches in soils containing 50% ormore of shingle or small size boulders upto 30 cm size, lift upto 1.50 m and stacking the excavated soil not more than 3 m clear from the edge of the excavation and returning the stacked soil in 15 cm layers when required, into plinth, sides of foundation etc consolidating each deposited layer by ramming and watering and then disposing of all surplus excavated soil as directed within a lead of 50m. | 17.14 | 281.30 | Cum | 4820.08 | SH: EW, 1-4 |
| 104 | 2 | Providing and laying in foundations and plinth cement concrete 1:5:10 (1 cement: 5 coarse sand: 10 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. | 2.05 | 4296.20 | Cum | 8794.32 | SH: CC, 1-1 |
| (6) | 3 | Providing and laying in foundations and plinth cement concrete 1:3:6 (1 cement: 3 coarse sand: 6 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. | 1.86 | 5323.20 | Cum | 9917.12 | SH: CC, I-4 |
| 7 | 4 | Reinforced concrete work in foundations, footings, bases of columns etc. and mass concrete excluding cost of centring, shuttering and reinforcement in : a) M20 (1 cement : 1.5 coarse sand : 3 stone aggregate 20 mm nominal size) | 1.17 | 7801.90 | Cum | 9128.22 | SH: RCC, 1-1 |
| - 1 | 5 | Reinforcement cement concrete work in columns, pillars, piers, abutments, post and struts etc upto floor two level including finishing and plastering the exposed surface with cement mortar 1:3 (1 cement:3 fine sand) of thickness not exceeding 6 mm to give a smooth and even surface but exluding cost of centring, shuttering and reinforcement. a) M20 (1 cement: 1.5 coarse sand: 3 stone aggregate 20 mm nominal size) | 1.17 | 9013.10 | Cum | 10545.33 | SH: RCC, 1-7 |
| | 9 | Reinforced cement concrete work in lintels, beams and bresumers up to floor two level including finishing and plastering the exposed surface with cement mortar1:3 (Icement:3finesand) of thickness not exceeding 6mm to give a smooth and even surface but excluding cost of centering, shuttering and reinforcement. a) M20 (I cement: 1.5 coarse sand: 3 stone aggregate 20 mm nominal size). | 2.54 | 8915.10 | Cum | 22626.52 | SH: RCC, 1-5 |
| | _ | Centring and shuttering including strutting, propping etc and removal of form work for | | | | | |
| | | a) Foundation, footings, bases of columns etc. and mass concrete | 11.96 | 348.10 | Sqm | 4163.28 | SH: RCC, 1-12 |
| | | b) Lintels, beams, girders, bressumers and cantilevers etc. | 29.70 | 458.60 | Sqm | 13620.42 | SH: RCC, 1-12 |
| | | c) Column, pillars, posts and struts etc. | 30.50 | 584.60 | Sqm | 17829.13 | SH: RCC, 1-12 |
| The second second | | | | | | | |

| SI. | SI. No. | Sub-Head and Items of work | Qty | Rate | Unit | Amount | Remarks |
|----------|---------|---|------------------------------------|-----------|-------|--------------|-----------------|
| | 1 | 2 | 3 | 4 | 5 | 9 | 7 |
| | ∞ | Reinforcement of RCC work including bending, binding and placing in position complete. b) Tor/TMT stee | 541.30 | 88.60 | Kg | 47959.16 | SH: RCC, 1-19 |
| | 6 | Half brick masonry (with best available local bricks) in cement mortar 1:4 (1 cement : 4 fine sand) in foundations and plinth . | 37.80 | 988.00 | Cum | 37346.40 | SH: BW, I-12 |
| | 10 | Extra for half brick work with best available local bricks in superstructure above plinth level up to floor two level. | 37.80 | 39.10 | Cum | 1477.98 | SH: BW, I-13 |
| 17 | 11 | 12 mm cement plaster 1 : 4 (1 cement : 4 fine sand). | 75.60 | 156.10 | Sqm | 11801.16 | SH: Fin, 1-2 |
| , , | 12 | Colour washing such as green, blue or buff on new work (two or more coats) including a base coat of white washing with lime to give an even shade | 108.00 | 21.70 | Sqm | 2343.60 | SH: Fin, 1-42 |
| | | Sub-Total (A) | | | | ₹ 202,372.72 | |
| | | CARRIAGE OF MATERIAL | | | | | |
| 1 | 13 | Loading and Unloading of Stone Boulder/Stone aggregates / Sand / Kanker Moorum/Lime/Shingle/Surki/Earth/Excavated Rock and Kerb Stones by Manual Means for hill roads | 25.88 | 214,00 | Cum | ₹ 5,538.86 | SH: Carr, 1-1.6 |
| <u> </u> | 14 | Loading and Unloading of Cement/ Steel / Structural Steel/RC Pipe/ Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hill roads. | 9.81 | 264.00 | TM | ₹ 2,589.29 | SH: Carr, 1-1.6 |
| | 15 | Cost of Haulage Excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | | | |
| | a) | a) Surfaced Road | | | | | |
| | | Cement/Steel [From Guwahaty to Itanagar 410 km] [Rate = $410 \times 10.5 = Rs. 4305.00$] | 9.81 | 4305.00 | MT/Km | ₹ 42,223.08 | SH: Carr, 1-1.8 |
| | | Bricks [From Bishwanath Chariali to Itanagar 105 km] [Rate = $105 \times 10.5 = Rs. 1102.50$] | 7.27 | 1102.50 | MT/km | ₹ 8,014.33 | SH: Carr, 1-1.8 |
| | | Sand/Agg [25 km] [Rate = $25 \times 10.5 = Rs. 262.50$] | 25.88 | 262.50 | MT/km | ₹ 6,794.17 | SH: Carr, 1-1.8 |
| | (q | b) Unsurfaced Graveled Road | | | | | |
| | | Sand / Agg [5 km] [Rate = $5 \times 12.60 = Rs. 63.00$] | 25.88 | 63.00 | MT/km | ₹ 1,630.60 | SH: Carr, 1-1.8 |
| | (c) | Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. [2km] [Rate = $2 \times 25.40 = Rs. 50.80$] | 25.88 | 50.80 | MT/km | ₹ 1,314.83 | SH: Carr, 1-1.8 |
| | | Sub-Total (B) | | | | ₹ 68,105.16 | |
| | | Cost | Cost for $30.00 \text{ m} = [A+B]$ | = [A+B] = | | ₹ 270,477.88 | |

₹ 9,020.00

Cost per Mtr =

Name of Work :- C/o Boundary wall with Coping for Normal Non-Residential and Residential (Type-V and above Type) Buildings.

[Calculation for Wall length of 30.00 Mtrs]

| Item No. | Description of Item | No. | Length | Breadth | Height | Quantity |
|-------------|---|-----|--------|---------|-----------|------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 1 | Earth work in excavation in foundation and trenches | | | | | - |
| | Columns | 13 | 1.00 | 1.00 | 1.10 | 14.30 Cum |
| | Walls | 12 | 1.50 | 0.45 | 0.35 | 2.84 Cum |
| | Total | | | | | 17.14 Cum |
| 2 | Providing and laying PCC 1:4:8 in foundation | | | | | |
| | Columns | 13 | 0.80 | 0.80 | 0.10 | 0.83 Cum |
| | Walls | 12 | 2.25 | 0.45 | 0.10 | 1.22 Cum |
| | Total | | | | | 2.05 Cum |
| 3 | Providing and laying PCC 1:3:6 in foundation | | | | | |
| | Below plinth beam | 12 | 2.25 | 0.23 | 0.30 | 1.86 Cum |
| | Total | | | | | 1.86 Cum |
| 4 | RCC Work in Foundation footings. | 13 | 0.60 | 0.60 | 0.25 | 1.17 Cum |
| | Total | | | | | 1.17 Cum |
| 5 | RCC Work in Columns | 13 | 0.23 | 0.23 | 2.55 | 1.75 Cum |
| | Total | | | | | 1.75 Cum |
| 6 | RCC work in Beams | 12 | 2.25 | 0.23 | 0.30 | 1.86 Cum |
| | Coping | 12 | 2.25 | 0.25 | 0.10 | 0.68 Cum |
| | Total | | | | | 2.54 Cum |
| 7 | Centering and shuttering | | | | | ¥ |
| a) | Foundation, footings, | 13 | 3.20 | | 0.10 | 4.16 Sqm |
| | | 13 | 2.40 | | 0.25 | 7.80 Sqm |
| 1. | Total | 2.4 | 2.05 | | 0.55 | 11.96 Sqm |
| b) | Beams | 24 | 2.25 | | 0.55 | 29.70 Sqm 29.70 Sqm |
| c) | Column | 13 | 2.55 | | 0.92 | 30.50 Sqm |
| () | Total | 13 | 2,33 | | 0.72 | 30.50 Sqm |
| | | | | | | |
| 8 | Reinforcement for RCC | | | | | |
| | Column Footing 10mm dia bars 5 Nos both ways | 130 | 0.60 | @ | 0.62 kg/m | 48.36 Kg |
| | Col Main bars 12mm dia 4 Nos | 52 | 3.30 | @ | 0.89 kg/m | 152.72 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 208 | 0.85 | @ | 0.39 kg/m | 68.95 Kg |
| | Beam reinforcement 12mm dia 4 Nos | 4 | 30.60 | (a) | 0.89 kg/m | 108.94 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 180 | 0.85 | @ | 0.39 kg/m | 59.67 Kg |
| | Coping bar 10mm dia 2 Nos | 2 | 30.60 | @ | 0.62 kg/m | 37.94 Kg |
| | Stirrups 8 mm dia @ 150mm C/C | 208 | 0.48 | @ | 0.39 kg/m | 38.94 Kg |

| | | | | | | 515.52 Kg |
|----|---|----|-------|------|---------|-----------|
| | Add 5% for Wastage and overlapping | | - | | | 25.78 Kg |
| | | | | | Total = | 541.30 Kg |
| 9 | Half Brick work in cement mortar 1:4 | 12 | 2.25 | 1.40 | | 37.80 Sqm |
| 10 | Extra for Brick work in Super structure | | | | | 37.80 Sqm |
| 11 | 12mm Cement Plaster 1:4 CM | 24 | 2.25 | | 1.40 | 75.60 Sqm |
| 12 | Colour washing | 2 | 30.00 | | 1.80 | 108.00 Kg |

CARRIAGE OF MATERIAL

| 13 | Loading and Unloading of Stone Boulder I Stone aggregates / Sand I Kankerl Moorum/ Lime / Shingle ISurkii EarthI Excavated Rock and Kerb Stones by Manual Means forhillroads | | | 25.88 |
|----|--|--|--|-------------|
| 14 | Loading and Unloading of Cement I Steel I Structural Steel I RC Pipe I Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hil Iroads. | | | 9.81 |
| 15 | Cost of Haulage Excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | |
| a) | Surfaced Road | | | |
| | Cement/Steel | | | 9.81 |
| | Bricks | | | 7.269230769 |
| | Sand/Agg | | | 25.88 |
| b) | Unsurfaced Graveled Road | | | |
| | Sand / Agg | | | 25.88 |
| c) | Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. | | | 25.88 |


TC STATEMENT

Name of work: C/o Boundary wall with Coping for Normal Non- Residential and Residential (Type-V and above Type) Buildings.

| | | | | | | | | | Agent was the first of the firs | APPROPRIATE CARCING CONTRACTOR STATEMENT OF THE CONTRACTOR CONTRAC | promise and polymetric participation of the promise and the pr |
|---------------------------------|--|---|--|---|---|--|----------|-----------|--|--|--|
| Item | Trem of Works | Qty of Work | Unit | Cement | ent | Sa | Sand | Aggregate | egate | Br | Bricks |
| Zo. | | done | | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty |
| - | PCC 1:5:10 | 2.05 | Cum | 0,13 | 0.27 | 0.47 | 96.0 | 0.89 | 1.82 | | |
| 2 | PCC 1:3:6 | 1.86 | Cum | 0,22 | 0.41 | 0.47 | 0.88 | 0.89 | 1.66 | | |
| 3 | RCC in Foundation (M20) | 1.17 | Cum | 0.4 | 0.47 | 0.43 | 0.50 | 0.85 | 66.0 | | |
| 4 | RCC in Column (M20) | 1.75 | Cum | 0.42 | 0.74 | 0.47 | 0.82 | 0.85 | 1.49 | | |
| 5 | RCC in Beams (M20) | 2.54 | Cum | 0.42 | 1.07 | 0.47 | 1.19 | 0.85 | 2.16 | | |
| 9 | Half brick masonry in 1:4 CM | 37.80 | Cum | 0.078 | 2.95 | 0.267 | 1.01 | | | 50 | 1890 |
| 7 | 12mm Cement Plaster in 1:4 CM | 75.60 | Sqm | 0.0446 | 3.37 | 0.154 | 1.16 | | | | |
| 8 | Reinforcement for RCC | 541,30 | Kg | | | | | | | | |
| | | | | | 9.27 MT | | 6.53 Cum | | 8.12 Cum | | 1890 Nos |
| and independent and independent | CONTRACTOR OF A PRINCIPAL PRINCIPAL PRINCIPAL DESCRIPTION OF PRINCIPAL PRINC | CONTROL OF THE PROPERTY OF THE PARTY OF THE | STREET, STREET | CONTROL OF THE PROPERTY OF THE PARTY OF THE | CONTRACTOR DESCRIPTION OF THE PROPERTY OF THE | CONTROL OF THE PROPERTY OF THE | | | | | |

| S |
|------|
| ria |
| ate |
| E |
| e 0 |
| riag |
| Car |

| | 9.27 MT | $0.54 \mathrm{MT}$ | 9.81 MT | 10.45 MT | 15.43 MT | 25.88 MT | 7.27 MT |
|---------------|---------|---------------------|---------|----------|-----------|--|---------|
| | | | | 6.53 Cum | 8.12 Cum | 14.65 Cum | |
| | Cement | Steel | | Sand | Aggregate | Name of the last o | Bricks |
| of Materials: | ٠ | | | | | | |



Division:-Sub-Division:-

ABSTRACT OF COST-ORIGINAL ESTIMATE

State:- A.P.

Branch:- B&R

Name of Work: Providing and fixing Chain Link fencing for Residential Buildings (Type-I to Type-IV buildings).

| Earth work in excavation in foundation and trenches in soils containing 50% ormore of shingle or small size boulders upto 30 cm size, lift upto 1.50 m and stacking the excavated soil not more than 3 m clear from the edge of the excavation and returning the stacked soil in 15 cm layers when required, into plinth, sides of foundation etc consolidating each deposited layer by ramming and watering and then disposing of all surplus excavated soil as directed within a lead of 50m. Providing and laying in foundations and plinth cement concrete 1: 4: 8 (1 cement: 4 coarse sand 8 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. Providing and laying in foundations and plinth cement concrete 1: 2: 4 (1 cement: 2 coarse sand 4 graded stone aggregate 20 mm nominal size) excluding the cost of centring and shuttering. Providing and laying in foundations and plinth cement concrete 1: 2: 4 (1 cement: 2 coarse sand 4 graded stone aggregate 20 mm nominal size) excluding the cost of centring and shuttering. A) Foundation and plinth. Centring and shuttering including strutting, propping etc and removal of form work for a) Lintels, beams, girders, bressumers and cantilevers etc. b) Column, pillars, posts and struts etc. b) Column, pillars, posts and struts etc. b) Tor/TMI steel Half brick masonry (with best available local bricks) in cement mortar 1:4 (1 cement: 4 fine sand) in foundations and plinth. Seel work in single section inclding cutting, hoasting, fixing in position and applying a priming coat of red lead paint. Providing and fixing G.Lchain link fencing of 10 SWG GI wire 75 x 75 mesh diagonal netting and |
|---|
| small size boulders upto 30 cm size, lift upto 1.50 m and stacking the excavated soil not more than 3 m clear from the edge of the excavation and returning the stacked soil in 15 cm layers when required, into plinth, sides of foundation are consoliditing each deposited layer by ramming and watering and then disposing of all surplus excavated soil as directed within a lead of 50m. Providing and laying in foundations and plinth cement concrete 1: 4: 8 (I cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size) excluding the cost of centring and shuttering. A) Foundation and plinth. A) Foundation and plinth. A) Foundations and plinth cement concrete 1: 2: 4 (I cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) excluding the cost of centring and shuttering. A) Foundation and plinth. B) Earns Centring and shuttering including strutting, propping etc and removal of form work for a) Lintels, beams, girders, bressumers and cantilevers etc. b) Column, pillars, posts and struts etc. E) Column, pillars, posts and struts etc. Reinforcement of RCC work including bending, binding and placing in position complete. b) Tor/TMT steel Half brick masonry (with best available local bricks) in cement mortar 1:4 (I cement: 4 fine sand) in foundations and plinth. Steel work in single section inclding cutting, hoasting, fixing in position and applying a priming Selel work in single section inclding cutting, hoasting, fixing in position and applying a priming Providing and fixing G1. Chain link fencing of 10 SWG GI wire 75 x 75 mesh diagonal netting and weighing 2.10 Kg/5qm complete as per the direction of Engineer-in-charge. |

| 01 7 | SI. No. | Sub-Head and Items of work | Qty | Rate | Unit | Amount | Remarks |
|----------|------------|--|----------|---------|-------|--------------|-----------------|
| | - | 2 | 3 | 4 | 5 | 9 | 7 |
| | | b) G.I.staples 10 cm long (10 SWG) | 65.00 | 2,00 | Each | 325.00 | SH: MR |
| | 10 | 12 mm cement plaster 1:4 (1 cement: 4 fine sand). | 24.30 | 156.10 | Sqm | 3793.23 | SH: Fin, 1-2 |
| | 11 | Applying priming coat with ready mixes primer of approved brand and manufacture on steel work. | 3.51 | 33.50 | Sqm | 117.59 | SH: Fin, 1-65 |
| | 12 | Painting (two or more coats) with aluminium paint of approved brand and manufacture on new work to give an even shape. | 3.51 | 81.30 | Sqm | 285.36 | SH: Fin, I-82 |
| | | Sub-Total (A) | | | | ₹ 115,038.66 | |
| | | CARRIAGE OF MATERIAL | | | | | |
| | 13 | Loading and Unloading of Stone Boulder/ Stone aggregates / Sand / Kanker Moorum/ Lime / Shingle/Surki / Earth/ Excavated Rock and Kerb Stones by Manual Means for hill roads | 7.57429 | 214.00 | Cum | ₹1,620.90 | SH: Carr, 1-1.6 |
| | 14 | Loading and Unloading of Cement/ Steel / Structural Steel/RC Pipe/ Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hill roads. | 3.145517 | 264.00 | MT | ₹ 830.42 | SH: Carr, 1-1.6 |
| | 15 | Cost of Haulage Excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | | | |
| | a) | Surfaced Road | | | | | |
| | | Cement/Steel [From Guwahaty to Itanagar 410 km] [Rate = $410 \times 10.5 = Rs. 4305.00$] | 3.15 | 4305.00 | MT/Km | ₹ 13,541.45 | SH: Carr, I-1.8 |
| | | Bricks [From Bishwanath Chariali to Itanagar 105 km] [Rate = $105 \times 10.5 = Rs. 1102.50$] | 2.338462 | 1102.50 | MT/km | ₹ 2,578.15 | SH: Carr, I-1.8 |
| | | Sand/Agg [25 km] [Rate = $25 \times 10.5 = Rs$, 262.50] | 7.57 | 262.50 | MT/km | ₹ 1,988.25 | SH: Carr, 1-1.8 |
| | (q | Unsurfaced Graveled Road | | | | | |
| | | Sand / Agg [5 km] [Rate = 5 x 12.60 = Rs. 63.00] | 7.57 | 63.00 | MT/km | ₹ 477.18 | SH: Carr, I-1.8 |
| | c) | Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. [2km] [Rate = $2 \times 25.40 = Rs. 50.80$] | 7.57 | 50.80 | MT/km | ₹ 384.77 | SH: Carr, 1-1.8 |
| | | Sub-Total (B) | | | | ₹ 21,421.13 | |
| Military | C | Grand Total [A+B] | | | | ₹ 136,459.79 | |

Cost per Mtr =

₹ 4,550.00

Details of Measurement

Name of Work :- Providing and fixing Chain Link fencing for Residential Buildings (Type-I to Type-IV buildings)

[Calculation for Wall length of 30.00 Mtrs]

| ltem No. | Description of Item | No. | Length | Breadth | Height | Quantity |
|-------------|--|-----|--------|----------|-----------|-----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 1 | Earth work in excavation in foundation and trenches | | | | | |
| | For CC post. | 13 | 0.45 | 0.45 | 0.85 | 2.24 Cum |
| | For beams | 12 | 1.90 | 0.30 | 0.25 | 1.71 Cum |
| | Total | | | | | 3.95 Cum |
| 2 | Providing and laying PCC 1:4:8 in foundation | | | | | |
| | For CC post. | 13 | 0.45 | 0.45 | 0.10 | 0.26 Cum |
| | For beams | 12 | 2.25 | 0.30 | 0.10 | 0.81 Cum |
| | Total | | | | | 1.07 Cum |
| 3 | Providing and laying PCC 1:2:4 in foundation | | | | | |
| | Post | 13 | 0.23 | 0.23 | 1.35 | 0.93 Cum |
| | Total | | | | | 0.93 Cum |
| 4 | Providing and laying in foundations and plinth cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) excluding the cost of centring and shuttering. | 12 | 2.25 | 0.20 | 0.30 | 1.62 Cum |
| | Total | | | | | 1.62 Cum |
| 5 | Centering and shuttering | | | | | |
| a) | Beams | 24 | 2.25 | | 0.10 | 5.40 Sqm |
| | | 24 | 2.25 | | 0.30 | 16.20 Sqm |
| 1) | Total | 12 | 0.00 | | 1.25 | 21.60 Sqn |
| b) | Column | 13 | 0.92 | | 1.35 | 16.15 Sqn |
| 6 | Reinforcement for RCC | | | | | 16.15 Sqm |
| | Beam reinforcement 12mm dia 4 Nos | 4 | 30.50 | @ | 0.89 kg/m | 108.58 Kg |
| | Column reinforcement 10mm dia 4 Nos | 52 | 1.40 | (a) | 0.62 kg/m | 45.14 Kg |
| | Stirrups Col 8 mm dia @ 200mm C/C | 65 | 0.95 | <u>a</u> | 0.39 kg/m | 24.08 Kg |
| | Stirrups beams 8 mm dia @ 150mm C/C | 150 | 1.05 | @ | 0.39 kg/m | 61.43 Kg |
| | | | | | | 239.22 Kg |
| | Add 5% for Wastage and overlapping | | | | | 11.96 Kg |
| | | | | | Total = | 251.18 Kg |
| 7 | Half Brick work in cement mortar 1:4 | 12 | 2.25 | 0.45 | | 12.15 Sqm |
| 8 | Steel work in single section inclding cutting | | | | | |
| | Angle iron 60x60x6mm | 13 | 1.80 | @ | 5.40 kg/m | 126.36 Kg |
| | | | | | 100 | 126.36 Kg |

| • | Add 5% for Wastage | | | | Total = | 6.32 Kg |
|--------------------|---|-------|-------|----------|-----------|---|
| | Total | | | | | 132.68 Kg |
| | | | | | | 1.3268 Qtl |
| 9 | Providing and fixing G.I.chain link fencing of 10 |) SWG | | | | *************************************** |
| | a) G.I.chain link fencing of 10 SWG | 30.00 | 0.90 | <u>@</u> | 2.10 kg/m | 56.70 Kg |
| | b) G.I.staples 10 cm long (10 SWG) | 13 | 5 | | | 65 Nos |
| 10 | 12mm Cement Plaster 1:4 CM | 24 | 2.25 | | 0.45 | 24.30 Sqm |
| | | | | | | 27 |
| 11 | Applying priming coat with ready mixed prime | 13 | 0.15 | | 1.80 | 3.51 Kg |
| | | | | | | |
| 12 | Painting with aluminium paint on steel work | 13 | 0.15 | | 1.80 | 3.51 Kg |
| 13 | Colour washing | 2 | 30.00 | | 0.45 | 27.00 Sqm |
| Description | CARRIAGE OF MATERIAL | | | | | |
| 14 | Loading and Unloading of Stone Boulder I | | | | | 7.57 |

| 14 | Loading and Unloading of Stone Boulder I Stone aggregates / Sand I Kankerl Moorum/ Lime / Shingle ISurkii EarthI Excavated Rock and Kerb Stones by Manual Means forhillroads | | | 7.57 |
|--|--|--|--|------|
| 14 | Loading and Unloading of Cement I Steel I Structural Steel I RC Pipe I Wooden Logs / Bricks / Bitumen and Timber etc. by Manual Means and Stacking for hil Iroads. | | | 3.15 |
| 15 | Cost of Haulage Excluding Loading and Unloading on hill roads. Haulage of materials by tipper excluding cost of loading, unloading and stacking | | | |
| a) | Surfaced Road | | | |
| | Cement/Steel | | | 3.15 |
| | Bricks | | | 2.34 |
| Note that the same of the same | Sand/Agg | | | 7.57 |
| b) | Unsurfaced Graveled Road | | | v |
| | Sand / Agg | | | 7.57 |
| c) | Katcha Track and Track in River Bedl Nallah Bed and Choe Bed. | | | 7.57 |


.

TC STATEMENT

Name of work: Providing and fixing Chain Link fencing for Residential Buildings (Type-I to Type-IV buildings).

| Item | Item of Works | Qty of Work | Unit | Cement | ent | Sa | Sand | Aggr | Aggregate | Bı | Bricks |
|------|-------------------------------|-------------|------|--------|---------|--------|----------|--------|-----------|--------|---------|
| No. | | done | | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty | Coeff. | Qty |
| 1 | PCC 1:4:8 | 1.07 | Cum | 0.17 | 0.18 | 0.47 | 0.50 | 0.89 | 96.0 | w | |
| 2 | RCC in Beams (M20) | 1.62 | Cum | 0.42 | 89.0 | 0.47 | 0.76 | 0.85 | 1.38 | | |
| 3 | Half brick masonry in 1:4 CM | 12.15 | Sqm | 0.078 | 0.95 | 0.267 | 0.32 | | | 20 | 809 |
| 4 | 12mm Cement Plaster in 1:5 CM | 24.30 | Sqm | 0.0446 | 1.08 | 0,154 | 0.37 | | | | |
| rv | Reinforcement for RCC | 251.18 | Kg | | | | | | | | 20. |
| | | | | | 2.89 MT | | 1.96 Cum | | 2.33 Cum | | 808 Nos |

| | 2.89 MT | 0.25 MT | 3.15 MT | 3.14 MT | 4.43 MT | 7.57 MT | 2.34 MT | |
|------------------------|---------|---------|---------|----------|-----------|-----------|---------|--|
| | | | | 1.96 Cum | 2.33 Cum | 4.30 Cum | | |
| | Cement | Steel | | Sand | Aggregate | reducers. | Bricks | |
| Carriage of Materials: | | | | | | | | |





GOVERNMENT OF ARUNACHAL PRADESH FINANCE, PLANNING & INVESTMENT DEPARTMENT BLOCK No. 1, 4TH FLOOR: CIVIL SECRETARIAT: ITANAGAR

OFFICE MEMORANDUM

No. PD(SPD)-63/CCI/2015-16

Dated, Itanagar the 15th January 2019

It has been observed that in many cases, estimates are prepared on higher rate with higher specification but are implemented on lower specification at site. Further, there is no uniformity and standardisation of construction of Govt. buildings by various departments.

Hence, in order to ensure uniformity and standardisation of construction of both residential and non-residential buildings implemented by various departments of State Government, Cabinet Committee on Infrastructure, Govt. of A.P. has approved the following:

1. All works departments should follow CPWD Plinth Area Rate 2012 with cost index approved by the concerned Chief Engineer of PWD for their respective jurisdiction within the State for estimation of cost of both residential and non-residential buildings as attached in the Annexure-1. PWD Department shall notify the zone wise cost index every year for the entire state by 1st April which shall be followed by all line departments in letter and spirit. The cost index shall be prepared by adopting the format of calculation of cost index developed by CPWD attached in the Annexure – 4. It was also enjoined that in the calculation of cost index, actual cost of material at the location shall be assessed and such assessment must invariably take into account the reduction in cost of carriage resulting from improved road communication to the place under consideration.

2. The rate of RCC Framed Structure with specification in Annexure-II shall be adopted for important non-residential as well as for residential buildings of Type V and above or for the specific building with prior approval of Government of Arunachal Pradesh.

(POD)



- The rate of RCC Framed Structure with specification in Annexure-V shall be adopted for normal multiple storied residential and nonresidential buildings.
- 4. The rate of Load Bearing Construction with specification in Annexure-V shall be adopted for construction of single storied/double storied non-residential buildings as well as for residential buildings of Type-I to Type-IV and PHCs, CHCs and school buildings upto secondary level (both classrooms and hostels) with CGI sheet / slab roofing.

The Cabinet Committee on Infrastructure Govt. of A.P. has also observed that henceforth the specification in **Annexure - II** or **Annexure - V** shall form a part of tender document in the process of implementation of building projects as applicable for uniform adherence to specification as sanctioned by Government of A.P.

While according Administrative Approval and Expenditure Sanction, it shall be the duty of Concerned Secretary/Commissioner that the aforesaid guidelines are followed in letter and spirit.

(KalingTayeng), IAS
Development Commissioner (FP&I)
Govt. of AP., Itanagar

Memo No. PD(SPD)-63/CCI/2015-16 Copy to: Dated, Itanagar the 15th January 2019

- 1. The Commissioner to Hon'ble Governor, Arunachal Pradesh, Itanagar.
- 2. The Secretary to HCM, Arunachal Pradesh, Itanagar.
- 3. PS to HDCM, Aruanachal Pradesh, Itanagar.
- 4. PS to Cabinet Ministers, Government of Arunachal Pradesh
- 5. Under Secretary to Chief Secretary, Govt. of A.P, Itanagar.
- 6. All Commissioners/Secretaries/Special Secretaries, Arunachal Pradesh
- 7. All Chief Engineers/Directors/Superintend Engineers/Executive Engineers of all Zones, Arunachal Pradesh
- 8. Secretary Finance for information and necessary action please

(Himanshu Gupta), IAS

Special Secretary(Planning & Investment)

Govt of A.P, Itanagar

PLINTH AREA RATES AS ON 01.10.2012

ANNEXURE - 1

| S. No. | Description | Office/College/Hospital | Schools | Hostels | Residenti |
|-----------|--|-------------------------|--------------|-----------|-----------|
| - | | 3 | 4 | 5 | 6 |
| 1.0 (A) | RCC FRAMED STRUCTURE (Specifications as per Annexure –II) | Rate | s in Rs. per | sq. metre | |
| 1.1(A) | RCC framed structure upto six storeys | | | T | T |
| 1.1.1(A) | Floor ht. 3.35 mtr. | 23500 | 17000 | | |
| 1.1.2 (A | Floor ht. 2.90 mtr. | 20000 | 17000 | 16500 | |
| 1.0(B) | RCC FRAMED STRUCTURE (Normal Buildings) (Specifications as per Annexure –V) | | | 16500 | 16000 |
| 1.1 (B) | RCC framed structure upto six storeys | | | | |
| 1.1.1(B) | Floor ht. 3.35 mtr. | 19000 | 15200 | | |
| 1.1.2 (B) | Floor ht. 2.90 mtr. | | 10200 | 15000 | 14500 |
| 1.2 | EXTRAS FOR | | | 15000 | 14300 |
| 1.2.1 | Every additional storey over six storeys upto nine storeys | 560 | 560 | 560 | 560 |
| 1.2.2 | Every additional storey over nine storeys upto twelve storeys | 580 | 580 | 580 | 580 |
| 1.2.3 | Every 0.3 mt. additional height of floor above normal floor height of 3.35 mt./ 2.90 mts. | 270 | 270 | 270 | 270 |
| 1.2.4 | Every 0.3 mt. higher plinth over normal plinth height of 0.6 mt. (on G.F. area only) | 270 . | 270 | 270 | 270 |
| .2.5 | Every 0.30 mt. deeper foundations over normal depth of 1.20 metre (on G.F. area only) | 270 | 270 | 270 | 270 |
| 2.6 | Making stronger foundations to take load of one additional floor at a later date (on area of additional floor only) | 2270 | 2270 | 2270 | 2270 |
| 1 | Strip foundations in poor soil having bearing capacity less than 10 tonnes/ sqmt. (on G.F. area only) | 520 | 520 | 520 | 520 |
| 8.8 | Resisting Earthquake forces | 1140 | 1140 | 11.10 | |
| .9 | R.C.C. Raft foundations (ground floor only) | 6450 | 6450 | 6450 | 6450 |

| 1.2.10 | Pile foundation up to a depth of 15 mts | 11750 | 11750 | 11750 | 11750 |
|---------|---|---------|-------|-------|-------|
| | (on ground floor area only.) | | | | |
| 1.2.11 | Stronger structural members to take heavy load above 500 Kgs./sqm. upto 1000 Kgs./Sqm. | 1500 | 1500 | 1500 | 1500 |
| 1,2.12 | Larger modules over 35 sqm. | 1500 | 1500 | 1500 | 1500 |
| 1.3 | BASEMENT FLOOR | | | | |
| 1.3.1 | Floor ht. 3.35 mtrs with normal water proofing. | 19000 | - | - | - |
| 1.3.2 | EXTRA FOR BASEMENT WITH | , | | | |
| 1.3.2.1 | Every 0.3 mt. addl. Height (above 3.35 mt.) | 2320 | | - | - |
| 1.3.2.2 | Reduction for every 0.5 m. less height of basement than normal height 3.35 mt. | (-1280) | - | - | - |
| 1.4 | FIREFIGHTING | | | | |
| 1.4.1 | With wet riser system | 500 | 500 | 500 | 500 |
| 1.4.2 | With sprinkler system | 750 | 750 | 750 | 750* |
| 1.5 | FIRE ALARM SYSTEM | | | | |
| 1.5.1 | Manual Fire Alarm System | ** | - | - | 300 |
| 1.5.2 | Automatic Fire Alarm System | 500 | 500 | 500 | 500* |
| 1.6 | Operation Theatre (OPD) (Extra provision) | 2150 | - | - | - |
| 1.7 | Pressurized mechanical ventilation system in the basements (with supply of Exhaust blowers) | 650 | 650 | 650 | 650 |
| 1.8 | STILT PORTION | | | | |
| 1.8.1 | Stilt Portion of Multistorey RCC structure (up to ht of 3.35m) Applicable area only | 9850 | 9850 | 9850 | 9850 |
| 1.8.2 | Every 0.30 mt additional height (above 3.35m) | 450 | 450 | 450 | 450 |

Note :- Rates marked as*under items 1.4.2 & 1.5.2 for residential building are NBC 2005 applicable for apartment houses more than 45m height.

| | No. Description | 1 | PARTITION AND ADDRESS OF | Reside | ntia | I | Residential | | | al |
|-------|--|----------------------------|--------------------------|--------|----------|--------|--------------------------------------|-------|-------|-------|
| 1 | | Office/Colle /Hospitals | ege | Scho | ols | Hostel | Type-I, II, II & servant Qtrs. | 1 | e –IV | 7 |
| 1 | 2 | 3 | | 4 | | 5 | 6 | | 7 | 8 |
| 2.0 | LOAD BEARING CONSTRUCTION | | | | | | | | / | 0 |
| 2.1 | Floor height 3.35 mt. | | - | | \dashv | | | +- | | |
| 2.1.1 | Single storeyed | 15000 | \dashv | 14000 | 1 | - | | + | | |
| 2.1.2 | Doubled storeyed | 14300 | + | 12200 | - | | - | + | - | - |
| 2.1.3 | Three storeyed | 15000 | \top | 14000 | - | - | - | | - | - |
| 2.1.4 | Four storeyed | 16000 | + | 14000 | - | - | | 1 | - | - |
| 2.2 | Floor height 2.90 mt. | | 1 | 11000 | + | - | | + | - | ~ |
| 2.2.1 | Single storeyed | - | \top | _ | + | 13300 | 11000 | - | | |
| 2.2.2 | Double storeyed | - | \top | - | | 11700 | 11600 | 128 | _ | 14000 |
| 2.2.3 | Three storeyed | - | + | | _ | 13300 | 11300 | 124 | - | 13100 |
| 2.2.4 | Four storeyed | _ | + | _ | _ | 14000 | 11600 | 128 | - | 13400 |
| 2.3 | Scooter & Cycles sheds | - | + | _ | + | - 1 | 12200 | 135 | - | 14300 |
| 2.4 | Garrages | - | + | - | + | | 10500 | 105 | - | 10500 |
| 2.5 | Extra for | | + | | + | - | 10000 | 1000 | 00 | 10000 |
| 2.5.1 | Every 0.3 mt. additional height above normal height 3.35 mt./2.90 mt. | 270 | | 270 | | 070 | | - | | |
| .5.2 | Every 0.3 mt. higher plinth over normal plinth height of 0.60 mt. (on ground floor area only) | 270 | | 270 | - | 270 | 270 | 270 | | 270 |
| 5.3 | Every 0.3 mt. deeper foundations over normal depth of 1.20 mt. (on G.F. area only) | 270 | | | | 270 | 270 | 270 | | 270 |
| 5.4 | Making stronger foundations to take load of one additional floor at a later date (on area of additional floor only) | | | 270 | | 70 | 270 | 270 | | 270 |
| .5 | Foundations on poor soils having bearing capacity less than 10 T/sqmt. | 780 | | 780 | 78 | 80 | 780 | 780 | 7 | 80 |
| .6 | Foundation on poor soils requiring under reamed pile 6 mt. long | 520 | - | 520 | 52 | 20 | 520 | 520 | 1 5 | 520 |
| 7 | R.C.C. Raft foundation (GF. area only) | 5600 | | 600 | 560 | | 5600 | 5600 | 50 | 600 |
| 8 | Pile foundation up to a depth of 15 mtr. (G. F. area only) | 6450 11750 | - | 750 | 1174 | | 6450 | 6450 | 64 | 150 |
| | Extra for resisting Earth-quake Forces | | 11 | 730 | 1175 | JU J | 11750 | 11750 | 11' | 750 |
| | In Zone V | 1050 | 10 | 50 | 1050 | | 1050 | 1050 | - | |

| SI. No. | Description | | Non -Resi | dential | | Residentia | - |
|---------|--|------------------------------|-----------|---------|---------------------------------------|-------------------|-----------------------------|
| 51.140. | Description | Office/College /Hospitals | Schools | Hostel | Type-I, II, III & servant Qtrs. | Type –IV Qtrs. | Type –V, VI and above |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| 2.6.2 | Buildings of two storeyes or more in Zone III & IV | 520 | 520 | 520 | 520 | 520 | 520 |
| 2.6.3 | Resisting earthquake forces in Zone II and single storey buildings in Zone III & IV | | | | | | |
| 2.7 | Stronger structural members to take heavy loads above 500 Kg /sqm. Up to 1000 Kg/sqmt. | 1500 | 1500 | 1500 | 1500 | 1500 | 1500 |
| 2.8 | Larger modules over 35 sqmt. | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 |
| 2.9 | Fire-fighting | | | | | | 700 |
| 2.9.1 | With wet riser system | 500 | 500 | 500 | 500 | 500 | 500 |
| 2.9.2 | With sprinkler system | 750 | 750 | 750 | 750 | 750 | 750 |
| 2.10 | Fire Alarm System | | | | | - | - |
| 2.10.1 | a) Manual Fire Alarm system | - | - | - | 270 | 270 | 270 |
| 2.10.2 | b) Automatic Fire Alarm system | 500 | 500 | 500 | - | - | - |
| 2.11 | O.P.D. Operation Theatre etc. | 2150 | - | - | - | - | _ |

Note: Rates for items are applicable on entire plinth area except for items 1.2.4, 1.2.5, 1.2.6, 1.2.7, 1.2.9, 1.2.10, 1.5, 1.6, 1.7, 1.8, 2.5.2, 2.5.3, 2.5.4, 2.5.5, 2.5.6, 2.5.7, 2.5.8, 2.8, 2.9, 2.10, and 2.11.

| S. No. | Description | Office & | Hospitals | Schools | Hostels | Type of Quarters I II III IV | | | | |
|---------|--|----------------------------|-----------|--|-----------------------------------|------------------------------|--------------------------|---------------------|----------|--------------|
| | 2 00000 | College | | | | I | II | Ш | IV | V,VI & above |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
| 3.0 | SERVICES. | | | | | | | | | |
| 3.1 | Internal water supply & sanitary installations | 4% | 10% | 5% | 15% with attached | 12% | 12% | 12% | 12% | 12% |
| | | | | | toilets, 10% with common toilets. | 70 6 | ige mean t of norn | s % age nal Buil | of build | ding .0B) |
| 3.2 | External service connections | 5% | 5% | 5% | 5% | 5% | 5% | 5% | 5% | 5% |
| 3.3 | Internal electric installations | 12 1/2% | 12 1/2% | 121/2% | 121/2% | 121/2% | 121/2% | 121/2% | 121/2% | 121/2% |
| | | | | | | service | The above connectication | | | de |
| 3.4 | Internal electric installations for laboratories of schools | - | - | 15% of building cost of normal building (1.0B) | 43. | - | | | - | |
| 3.5 | Internal electric installations for terminal building and other allied structures in airports | 15% of building cost | - | - | - | | - | - | - | - |
| 3.6 | Extra for: | | | | | | | | | |
| 3.6.1 | Power wiring and plugs | 4% | 4% | - | - | - | - | - | - | No. |
| 3.6.2 | Central Call bell system | 1% | - | - | - | - | - | - | - | _ |
| 3.6.3 | Lightening conductors | | | | | | | | | |
| 3.6.3.1 | Upto 4 storeyed building | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% |
| 3.6.3.2 | 5 to 8 storeys buildings | 0.33% | 0.33% | 0.33% | 0.33% | 0.33% | 0.33% | 0.33% | 0.33% | 0.339 |
| 3.6.3.3 | Beyond 8 storeyed buildings | 0.25% | 0.25% | 0.25% | 0.25% | 0.25% | 0.25% | 0.25% | 0.25% | 0.25% |
| 3.6.4 | Telephone conduits | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% | 0.5% |
| 3.6.5. | Centralized Intercom system | - | - | - | - | 1% | 1% | 1% | 1% | 1% |
| 3.6.6 | Computer conduiting | 0.5% | 0.5% | 0.5% | 0.5% | | | | | |
| 3.6.7 | Quality assurance | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |

Note:- Quality control charge of 1% should be taken in estimate only when client department request for TPI.

| Sl. No. | Type of lift | Capacity/ Persons | Weight | Speed in M/Sec. | Travel | Doors | Control | Price (Rs. In lacs) | Addl. Price for each additional floor (Rs.) |
|---------|------------------------------|----------------------|----------|--------------------|------------------|----------------|------------|------------------------|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 4.0 | LIFTS | | | | | | | | |
| 4.1 | Passenger lifts | | | | | | | | |
| 4.1.1 | Passenger lift | 8 | 544 Kg. | 1.0 | G+4 | Power operated | ACV VVF | 18.00 | 1,25,000.00 |
| 4.1.2 | Passenger lift | 8 | 544 Kg. | 1.5 | G+5 | Power operated | ACV VVF | 24.00 | 1,25,000.00 |
| 4.1.3 | Passenger lift | 13 | 884 Kg. | 1.0 | G+4 | Power operated | ACV VVF | 22.00 | 1,25,000.00 |
| 4.1.4 | Passenger lift | 13 | 884 Kg. | 1.5 | G+5 | Power operated | ACV VVF | 28.00 | 1,25,000.00 |
| 4.1.5 | Passenger lift | 16 | 1088 Kg. | 1.0 | G+4 | Power operated | ACV VVF | 28.00 | 1,50,000.00 |
| 4.1.6 | Passenger lift | 16 | 1088 Kg. | 1.5 | G+5 | Power operated | ACV | 34.00 | 1,50,000.00 |
| 4.1.7 | Passenger lift | 16 | 1088 Kg. | 2.5 | G+12 | Power operated | ACV VVF | 70.00 | 1,50,000.00 |
| 4.1.8 | Passenger lift (Bed lift) | 20 | 1360 Kg. | 0.75 | G ₁ 4 | Power operated | ACV VVF | 24.00 | 1,50,000.00 |
| 4.1.9 | Passenger lift | 20 | 1360 Kg. | 1.5 | G+5 | Power operated | ACV VVF | 32.00 | 1,50,000.00 |
| 4.1.10 | Passenger lift | 20 | 1360 Kg. | 2.5 | G+12 | Power | ACV VVF | 75.00 | 1,50,000.00 |
| 4.2 | Goods lifts (2 speed) | | | = | | | | | |
| 4.2.1 | | 1 Ton | - | 0.5 | G ₁ 4 | | | 26.00 | 85,000.00 |
| 4.2.2 | | 2 Ton | - | 0,5 | G ₁ 4 | | | 33.00 | 85,000.00 |
| 4.2.3 | | 3 Ton | - | 0.25 | G ₁ 4 | | | 41.00 | 1,00,000.00 |

Note:- 1. ACVVVF=AC variable voltage variable frequency.
2. Provision for lift may also be taken for the buildings having floor less than G+ 4.

| SI. No. | Description | Rates in Rupees |
|---------|--|-----------------|
| 5 | WATER TANK (RCC ONLY) | |
| 5.1 | Overhead tank without independent staging | 15/Litre. |
| 5.2 | Overhead tank upto staging height 20 metres | 25/Litre. |
| 5.3 | Overhead tank with staging height between 20 metres and upto 30 metres | 30/Litre. |
| 5.4 | Overhead tank with staging height between 30 metres and 40 metres | 35/Litre. |
| 5.5 | Underground sump | 15/Litre |

| Sl. No. | Description | Rates in Rupees |
|---------|--|-----------------|
| 6 | DEVELOPMENT OF SITE | |
| 6.1 | Levellling | 95/ sqm. |
| 6.2 | Internal roads & paths | 145/ sqm |
| 6.3 | Sewer | 110/ sqm. |
| 6.4 | Filter Water Supply | |
| 6.4.1 | Distribution lines 100 mm dia and below | 80/ sqm. |
| 6.4.2 | Peripheral grid 150 mm to 300 mm dia pipes | 60/ sqm. |
| 6.4.3 | Unfiltered water supply distribution lines | 45/ sqm. |
| 6.5 | Storm water drains | 85/ sqm. |
| 6.6 | Horticulture Operations | 80/ sqm. |
| 6.7 | Street lighting | |
| 6.7.1 | With fluorescent lamps | 95/ sqm. |
| 6.7.2 | With HPMV Lamps | 130/ sqm. |
| 6.7.3 | With HPSV Lamps | 165/ sqm. |
| 6.7.4 | Exit sign board i/c electric signage. | 85/ sqm. |

Note :-

- (1) The rates are per sqm. and are to be applied on the entire areas of the plinth/ plot to be developed.
- (2) These rates will apply to normal conditions and normal layout plans. If any extras are required due to nature of layout involving filling, cutting or bringing services, from large distances, then additional provision should be made.
- (3) Cost of bulk services water supply, sewage disposal e.g.
 - (a) Tube wells, pumps, open wells, treatment plant, extension of lines from source of local bodies, head works at water source etc.
 - (b) Sewage pumps, sewage treatment plants, septic tanks, extension of cut-fall sewer up to point of disposal etc. are not included in these rates. Extra provision depending upon site conditions may be made for these.
- (4) Cost of HT sub station equipments, LT distribution system, DG sets, pumps, air-conditioning and other specialized works like aesthetic external lighting with metal halide lamp & facade lighting, addressable fire alarm system, rising mains, UPS, aviation obstruction lights, external service connections, storage water cooler, IBMS, CCTV, access control system for security, solar water heating system, solar lighting etc. are not included in above rates and the same are to be taken as per actual based on functional / utility of the proposed building.
- (5) 1.0 (A) shall be adopted for GPO and GPRA.
 - 1.0 (B) may be adopted for other buildings.
- (6) The green measures considered for Civil & Electrical works
 - (a) Over deck insulation and Application of high SRI reflective paint on the roof.
 - (b) Masonry work in super structure with Autoclave Aerated Concrete (AAC) blocks/ fly ash bricks.
 - (c) Window with reflective glass coating / High performance double glazed unit.
 - (d) Paints with low VOC options.
 - (e) Rain water harvesting.
 - (f) Replacement of conventional pillar cock with pillar cock having infrared sensor and foam flow technology (in offices and Hospitals).
 - (g) AC plant with VVVF drives and ECBC complaint chillers, high efficiency motors, plant optimizers etc. (cost of plant not included.)
 - (h) Automated lighting controls with day light sensors and PIRs etc.

(R.K. Saraswat) Executive Engineer (TAS)-I CPWD, Nirman Bhawan, New Delhi (Mathura Prasad) Superintending Engineer (TAS) CPWD, Nirman Bhawan, (V.K. Rokde) Chief Engineer (CSQ) CPWD, Nirman Bhawan New Delhi

ANNEXURE-II

SPECIFICATIONS FOR RESIDENTIAL BUILDINGS

| Item no. | Item | Type I, II, III & Servant Qtrs. | Type-IV | Type-V/VI | Hostel |
|----------|-----------------|--|--|-------------|--------|
| 1.1 | Foundation | Bearing capacity 10 tonnes per sq. metre. | Applie | able to all | |
| 1.2 | | Type –spread foundation in RCC isolated /combined, continuous wall footing with lean concrete. | Арриса | aoic to an | |
| 1.3 | - | Depth upto 1.2 metres below ground level | | | |
| 2.1 | Super structure | RCC framed construction with filler walls in brick work or load bearing construction if brick/stone masonry with intermediate columns where found necessary. | National Action of the Control of th | | |
| 2.2 | | Internal partition-half brick masonry in cement mortar 1:4 | | | |

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI |
|------------------|--------------------|---|---|---|
| 3.1 3.1.1 | Frames Window | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with double rebate | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with double rebate/scratch proof aluminium sheets/poly- propylene windows | Same as Type IV |
| 3.1.2 | Door | T-Iron /Pressed steel/Pre-cast R.C.C. frames. | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with single rebate/factory manufactured precast RCC frames. | Same as Type IV |
| 3.2 3.2.1 | Shutters Window | M.S. tubular box section corrosion resistant coated shutters. Wire mesh shutters may also be provided at the discretion of Zonal Chief Engineer. | M.S. tubular box section corrosion resistant coated shutters. Wire mesh shutters may also be provided at the discretion of Zonal Chief Engineer/Scratch proof aluminium window. Shutters to match with frame. | Same as Type IV |
| 3.2.2 | Main Door | Double door, one with iron grill with wire mesh mosquito proof and other 35 mm thick panelled shutter with hard wood style and rail with panelling of pre-laminated particle board, one side decorative other side balancing. | Same as Type 1 to III. | Same as Type I to III except that panelling will be of both side decorative, pre-laminated particle board. |
| 3.2.3 | W.C/Bath room | Solid PVC shutters 28 mm thick | Same as Type I to III | Same as Type I to III |
| 3.2.4 | Kitchen door | Partly panelled and partly wire mesh with stainless steel wire mesh. The panelling with pre-laminated particle board, one side decorative-35 mm thick panelled shutter with hard wood style and rails. | Same as Type I to III | Partly panelled and partly wire mesh with stainless steel wire mesh. The panelling with prelaminated particle board, both sides decorative 35 mm thick panelled shutter with hard wood style and rails. |

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI |
|-------|---|--|--|--|
| 3.2.5 | Other doors | 35 mm thick panelled shutters with hard wood style and rail with panelling of prelaminated board, one side decorative. | Same as Type I to III | 35 mm thick panelled shutters with hard wood style and rail with panelling of pre laminated board, both sides decorative. |
| 3.3 | Fittings | Powder coated M.S. fittings/stainless steel fittings | Powder coated aluminium/ stainless stee! fittings | Same as type IV |
| 3.4 | Peep hole and security chain for external door only. | Yes | Yes | Yes |

In item no. 3 of Wood work, if any other option of local material is available, the same can also be used by the respective Chief Engineers.
 External sliding door bolt and handles will be in powder coated M.S. or stainless steel.
 Koba treatment on roofing in all type of quarters.

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI |
|----------------|--|---|--|--|
| 4.1 | Flooring Bedrooms/ living rooms | Grey/Beige color ceramic floor tiles (size 12" × 12" Matt finish) of approved design | Same as Type I to III | Grey/Beige color rectified - ceramic floor tiles (size 16" × 16" Matt finish) of approved design. |
| 4.2 | Kitchen, internal circulation area | Ceramic floor tiles (size 12" × 12" Matt finish) of approved design. | Same as Type 1 to III | Rectified ceramic floor tiles (size 16" × 16" Matt finish) of approved design. |
| 4.3 | Common circulation area, staircase | (i) Kota stone flooring and matching skirting. In staircase, single piece pre-polished kota stone slab with pre-finished nosing be used. (ii) Dado of ceramic tile light grey/dull green shade 12" × 12" size upto 120 cm ht. above skirting i/c green marble nosing. | Same as type I to III | Same as type IV |
| 4.4 | Kitchen work | Green marble pre-polished with pre-moulded nosing | Same as type I to III | Granite with pre-polished and premoulded nosing |
| 4.5 | Toilets | Ceramic floor tiles (Size 12"×12") Matt finish/anti skid of approved design. | Same as type I to III | Rectified ceramic floor tiles (size 16" × 16")Matt finish/ anti skid of approved design |
| 4.6 | Skirting/Dado in toilets | Ceramic white glazed tiles (min. size 8" × 12") upto door lintel level. | Same as type I to III | Ceramic white giazed tiles (min. size 8" × 12") upto ceiling ht. with decorative band of tiles. |
| 5.0 5.1 | Finishing External | Acrylic smooth exterior finish or washed stone grit plaster or exposed brick work | Premium Acrylic smooth exterior finish with additive of silicone or washed mosaic plaster in ordinary cement or exposed brick work | Premium Acrylic smooth exterior finish with additives of silicone or washed mosaic plaster in ordinary cement or exposed brick work. |
| 5.2 | Internal | All walls and ceilings to be treated with the 2 mm thick POP followed with a coat of acrylic/ oil bound distemper except ceiling which will be done with white wash. Synthetic enamel paint on all wood work and steel work. | Same as type I to III | All walls and ceilings to be treated with the 2 mm thick POP followed by plastic emulsion paint except ceiling which will be done with white wash. Synthetic enamel paint on all wood work and steel work. |

SPECIFICATIONS FOR BUILDINGS

Non-Residential

| S.No. | Description | Item no. | Office | | Hospitals | Schools |
|---|---|----------|--|---|--|--|
| 1 | 2 | 3 | 4 | | 5 | 6 |
| 1 FOUNDATIONS 1.1 Bearing capacity 10 tonnes/square n | | netre. | | | | |
| | | 1.2 | Type - Spread foundations isolated/ | combined | | |
| | | 1.3 | Depth Upto 1.2 metres below grou | nd level | | |
| 2. | SUPER STRUCTURES | 2.1 | RCC framed construction with filler masonry with intermediate columns | | | struction in brick/stone |
| | | 2.2 | Internal partition in brick masonry | | and the same of th | The state of the s |
| | | 2.3 | RCC chajjas, fins, jalis etc. | *************************************** | | |
| 3. | DOORS & WINDOWS | 3.1 | Frames of 2nd class Indian teakwood CPWD Specifications | l or equival | lent or T-iron frame, pressed | steel frame as per |
| | | 3.2 | Door shutters; Panelled type in 2nd Specifications | class teak v | vood or flush door with comr | nercial ply as per CPWD |
| | a de la companya de | 3.3 | Window shutters 2nd class Indian teak wood | wood. Fly & windows ground flo which prov | nutters 2nd class Indian teak proof shutters for all doors and iron grills for windows in or shall be provided for vision for extra rate will be eel windows. | class Indian Teak wood |
| | | 3.4 | Fittings | Anodized | aluminium or equivalent | |
| 4. | FLOORING | 4.1 | Main entrance hall terrazzo tiles, kota stone and the like. Lavatory blocks and corridors & some officers room. | kota stone corridors a stores, we | ance hall terrazzo tiles, & the like. Lavotory blocks and other rooms except ather-maker rooms etc. oring with dado upto 7'0" | Main entrance hall, staircase, lavatory blocks in-situ mosaic |
| | | ٠ | Mosaic limited upto 25% of total area. | rooms, the limited to | s & upto sill level in other flooring & dado to be 50% in ordinary cement n white cement. | |
| | | 4.2 | Rest of the area ordinary cement concrete | Rest of the | e area ordinary cement | Rest of the area ordinary cement concrete |
| 5. | ROOFING | 5.1 | Filling for drainage lime concrete | Filling for | drainage lime concrete | Filling of drainage lime concrete finished with brick tiles |
| | | 5.2 | Water-proofing treatment 4 course treatment finished with brick tiles | | ofing treatment 4 course finished with brick tiles. | Water-proofing treatment 4 course treatment finished with brick tiles. |
| 6. | FINISHING | 6.1 | External water proofing cement paint | External v | vater proofing cement paint | External water proofing cement paint |
| | | 6.2 | Internal Officers rooms & important rooms such as Committee Rooms dry distemper to be limited upto 25% of the total area. Rest either colour or white wash. Main entrance hall plastic emulsion paint or the like. (Low V.O.C) | operation rooms, suc X-ray room total area. wash. Mai | y distemper in doctors room, theatre other important ch as committee room, m etc. Limited upto 25% of Rest either colour or white n entrance hall, OPD Plastic paint or the like. (Low V.O.C) | principals room, Committee room etc. dry distemper. Rest of the area white or |
| | | 6.3 | Door & windows- painting | Doors & v | vindows painting | Doors & windows painting |

SPECIFICATIONS FOR RESIDENTIAL BUILDINGS

| Item no. | Item | Type I, II, III & Servant Qtrs. | Type-IV | Type-V/VI | Hoste |
|----------|-----------------|--|---------|------------|-------|
| 1.1 | Foundation | Bearing capacity 10 tonnes per sq. metre. | -JF- I | 13 pc 1711 | Hoste |
| 1.2 | | Type –spread foundation in RCC isolated /combined, continuous wall footing with lean concrete. | Applica | ble to all | |
| 1.3 | | Depth upto 1.2 metres below ground level | 1 | | |
| 2.1 | Super structure | | | | |
| 2.2 | | Internal partition-half brick masonry in cement mortar 1:4 | | | |

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI |
|--------------|--------------------|---|--|---|
| 3.1 3.1.1 | Frames Window | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with double rebate | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with double rebate/scratch proof aluminium sheets/polypropylene windows | Same as Type IV |
| 3.1.2 | Door | T-Iron /Pressed steel/Pre-cast R.C.C. frames. | Pressed steel frames made out of corrosion resistant coated sheet of 1.6 mm thick with single rebate/factory manufactured precast RCC frames. | Same as Type IV |
| 3.2 3.2.1 | Shutters Window | M.S. tubular box section corrosion resistant coated shutters. Wire mesh shutters may also be provided at the discretion of Zonal Chief Engineer. | M.S. tubular box section corrosion resistant coated shutters. Wire mesh shutters may also be provided at the discretion of Zonal Chief Engineer /Scratch proof aluminium window. Shutters to match with frame. | Same as Type IV |
| 3.2.2 | Main Door | Double door, one with iron grill with wire mesh mosquito proof and other 35 mm thick panelled shutter with hard wood style and rail with panelling of pre-laminated particle board, one side decorative other side balancing. | Same as Type I to III. | Same as Type I to III except that panelling will be of both side decorative, pre-laminated particle board. |
| 3.2.3 | W.C / Bath room | Solid PVC shutters 28 mm thick | Same as Type I to III | Same as Type I to III |
| 3.2.4 | Kitchen door | Partly panelled and partly wire mesh with stainless steel wire mesh. The panelling with pre-laminated particle board, one side decorative-35 mm thick panelled shutter with hard wood style and rails. | | Partly panelled and partly wire mesh with stainless steel wire mesh. The panelling with prelaminated particle board, both sides decorative-35 mm thick panelled shutter with hard wood style and rails. |

SCALE OF AMENITIES FOR GENERAL POOL ACCOMMODATION

| tem | SCALE OF AMEN | Type I | Type | 11 191 | e III Ty | pe IV | Type V/VI |
|-------|--|---|--------|--|--|--|--|
| No. | Kitchen Shelves in tiers not more than 400mm wide along one wall | Yes | Yes | Yes | ab la | overed cup boards ove sill level with pre- minated decoarative pard. | Same as Type IV |
| (ii) | 1 " thick Kitchen sink | Stainless steel sink without drain board size 610 X 510 mm with bowl depth 200 mm | 1 | Cuo | pe-I d | tainless steel sink with rain board size 510 X 040mm with bowl depth 00mm | Stainless steel sink of size 510 x 1040 mm with bowl depth of 250 mm with draining board/ vitreous china sink with draining board of size 600 x 450 x 250 mm |
| (iii) | Dado Ceramic glazed tiles for 60cm. above work top and around sunken floor | Yes | Yes | 5 | Zes . | Yes | Ceramic glazed tiles upto 60 cm above cooking platform all around |
| (iv) | Built in cupboard with open shelves below cooking platform shutter of pre-laminated particle board 18mm thick below window sill level of cooking platform along one wall | Yes | Ye | es | Yes | Yes with 2 drawers | Yes with 2 drawers |
| (v) | 1 .f standi | ng Yes | - | es | Yes | One in each Bed Room | One in each Be |
| 2(i | _ | One in each Bed Room 7'-00" hei | ight 7 | One in each Bed Room, 1'-00" neight | One in each Bed Room 7'-00" height | upto ceiling height | Room upto ceiling height |
| | | | | One | One | One | One |
| (ii | | | - | Kota Stone | - | Kota Stone | Marble |
| (i | thick projected with Ko stone/marble | | | | Stone | S Drapery rods | Drapery rods |
| G | iv) Curtain rods with brac | | | All rooms | All room | In bath, bed rooms a | nd In bath, bed |
| | v) Set of Pegs | In bath a bed room | | In bath an bed rooms | | ns wardrobes | rooms and wardrobes |

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI | |
|-------|---|--|---|--|--|
| 3.2.5 | Other doors | 35 mm thick panelled shutters with hard wood style and rail with panelling of prelaminated board, one side decorative. | Same as Type I to III | 35 mm thick panelled shutters with hard wood style and rail with panelling of pre laminated board, both sides decorative. | |
| 3.3 | Fittings | Powder coated M.S. fittings/ stainless steel fittings | Power coated aluminium/ stainless steel fittings | Same as type IV | |
| 3.4 | Peep hole and security chain for external door only. | Yes | Yes | Yes | |

- Note:
 1. In item no. 3 of Wood work, if any other option of local material is available, the same can also be used by the respective Chief Engineers.
 2. External sliding door bolt and handles will be in powder coated M.S. or stainless steel.
 3. Over deck insulation with PUF Slab/Koba treatment on roofing in all type of quarters.

| S No. | Item | Type I, II, III & Servant Qrs. | Type IV | Type V and VI | |
|-----------------|---|--|---|--|--|
| 4 4.1 | Flooring In rooms, kitchen, internal circulation area | Mosaic flooring and skirting with ordinary cement except in common circulation area and staircase | Same as Type 1 to III | Mosaic/Terrazzo tile flooring with white cement. In kitchen, ceramic tiles/marbles flooring | |
| 4.2 | Common circulation area, staircase | Kota stone flooring and matching skirting. In staircase, single piece Kota stone shall be used | Same as Type I to III | Same as Type IV | |
| 4.3 | Kitchen work top | Kota stone | Udaipur green märble/Granite stone | Granite stone | |
| 4.4 | Toilets | Mosaic | Ceramic Tiles | Ceramic Tiles | |
| 4.5 | Skirting/Dado | Ceramic glazed tiles in Indian Type WC upto 90 cm. height and bath room upto door jamb height. | Same as Type I to III | Ceramic glazed tiles upto ceiling height with a decorative band of tiles. | |
| 5.0 5.1 | Finishing External | Acrylic smooth exterior finish or washed stone grit plaster or exposed brick work | Premium Acrylic smooth exterior finish with additive of silicone or washed mosaic plaster in ordinary cement or exposed brick work | Premium Acrylic smooth exterior finish with additives of silicone or washed mosaic plaster in ordinary cement or exposed brick work. | |
| 5.2 | Internal | All walls and ceilings to be treated with the 2 mm thick POP followed with a coat of acrylic/ oil bound distemper except kitchen, bath & WC and all ceiling, which will be done with white wash. Synthetic enamel paint on all wood work and steel work. | All walls & ceiling to be treated with 2 mm thick POP followed with a coat of acrylic / oil bound distemper except kitchen, bath & WC and all ceilings, which will be done with white wash. Synthetic enamel paint on all wood work and steel work. | All walls & ceiling to be treated with 2mm thick POP plaster and cornices followed with a coat of plastic emulsion paint except kitchen, bath and WC and all ceilings, which will be done with white wash. Synthetic enamel paint on all wood work and steel work. | |

SCALES OF SANITARY FITTINGS FOR GENERAL POOL RESIDENTIAL QUARTERS

| Item No. | Item | Туре І | Туре П | Type III | Type IV | Type V/VI | |
|-------------|--|---|-----------------------|-----------------------|--|--|--|
| 1. | Indian W.C. Pan with flushing cistern | One WC Pan Orissa pattern with low level PVC Flushing Cistern | One Same as Type I | One same as Type I | One same as Type I | One + One for servant quarter | |
| 2. | European type W.C. with low level flushing cistern | - | - | - | One with low level PVC flushing cistern | One (syphonic type)with matching low level cistern | |
| 2(a) | Water Jet with low level European W.C. | - | - | - | One | One | |
| 3. | Wash basin with one tap each | One | One | One | Two mixer type for hot & cold water | Three mixer type for hot & cold water | |
| 4. | Tap (kitchen bath & W.C.) C.P. Brass/ PTMT bib cock | 4 PTMT | 4 PTMT | 4 C.P. brass | 5 C.P. brass | 12 (1 PTMT + 11 CP brass) | |
| 5 | Shower C.P. Brass / PTMT | One PTMT | One PTMT | One PTMT | Two C.P.brass | Three C.P. brass | |
| 6. | Towel rail C.P. Brass/ PTMT | One PTMT | One PTMT | One PTMT | Two C.P. brass | Two C.P. brass | |
| 7. | Mirror / Bevelled edge/ P.V.C. frame with PTMT glass shelf | One | One | One | Two | Three | |
| 8. | Soap rack (Nitch in W.C./ Bath) | One | One | One | Two | Three | |
| 9. | Liquid soap container | - | - | _ | Two | Three | |
| 10. | Storage tank | 500 ltr. , | 500 ltr. | 500 ltr. | 750 litre | 1000 litre + 500 litre for servant quarter | |
| 11. | Nitch with Kota stone sill in bath room | One | One | One " | Two | 3 + 1 for servant quarter | |

Note: Waste coupling in wash basins and grating over the floor trap shall be only of PTMT.

SPECIFICATIONS FOR ELECTRICAL INSTALLATION IN RESIDENTIAL QUARTERS

| Item No. | Description | TypeI | TypeII | ТуреШ | Type IV Type V (excluding servant quarter & Garage) | | Type VI (excluding servant quarter & garage) | Qtrs & Garage |
|----------|--|-------------------------|--------|-------|---|----|--|------------------|
| | | | 3 | 4 | 5 | 6 | 7 | 1. |
| 1. | Power Points (15 amperes, 6 pins | 2 | 3 | | 2 | 4 | 5 | - |
| 2. | MCB connected socket outlet for A.C. unit /Geyser complete | 1 | 1 | 1 | 2 | , | | 1 |
| | with wiring | 2 | 3 | 4 | 5 | 6 | 7 | 1 |
| 3. | Ceiling Fans | - | 1 | 1 | 1 | 1 | 1 | - |
| 4. | Exhaust Fans | 1 | | 1 | 1 | 2 | 3 | |
| 5. | Call bells | 1 | 1 | | 27 | 38 | 44 | 5 |
| 6. | Light/Fans/Call bell/5A Plug Points | . 17 | 20 | 23 | | 7 | 8 | 1 |
| 7. | F.I. Fittings excluding Tube and Starter | 2 3 | | 4 | 5 | | conduit wiring | |
| | Type of Wiring | Recessed Conduit wiring | | | Concealed conduit wiring | | | |
| 0 | EDB MCB Type | | | | | | | 1 |
| 8. | A. Single Phase | 1 | 1 | 1 | - | - | 1 | - |
| | B. 3 Phase | - | - | - | 1 | 1 | 2 | _ |
| - | Cable TV Point | 1 | 1 | 1 | 1 | 2 | 2 | _ |
| 9. | Telephone Point | - | - | - | 1 | 2 | | |

PROFORMA FOR CALCULATION OF COST INDEX

| S.No. | Description | | Unit | Rate as on 1.10. 2012 in Rs. | Weightage | Rate at the time of revision of cost Index | Cost Index |
|-------|--|----------------------------|-------------|------------------------------|-----------|---|---------------|
| 1. | BRICKS | | 1000 Nos. | 3867.00 | 8.00 | | |
| 2. | CEMENT(OPC) | | QTL. | 587.00 | 14.50 | | |
| 3. | STEEL a) 8 & 10 MM(TOR STEEL) b) 12 & 16 MM (TOR STEEL) | 50% 50% | QTL. | 4669.00 | 19.50 | | |
| 4. | AGGREGATE 20 MM SIZE | | CUM. | 1350.00 | 6.50 | | |
| 5. | SAND(COARSE SAND) | | CUM. | 1293.00 | 3.00 | | |
| 6. | FLOORING ITEMS (a) MOSAIC TILES (b) CERAMIC TILES (c) KOTA STONE (d) GRANITE STONE | 40% 40% 10% 10% | SQM. | 467.00 | 3.00 | | |
| 7. | PAINTS (a) SYNTHETIC ENAMEL PAINT (b) O.B.D. (c) PLASTIC EMULSION PAINT | 33.33% 33.33% 33.33% | LITRE | 151.00 | 3.00 | | |
| 8. | PLY AND COMM. WOOD (i) 12 MM THICK PARTICLE BOARD (ii) STEEL WINDOW STANDARD Z SECTION (iii) ALUMINIUM WINDOW | 33.33% 33.33% 33.33% | SQM. | 1476.00 | 5.00 | | |
| 9. | PIPES (i) 15 MM GI, PIPE (ii) 100MM SCI PIPES (iii) 20 MM Black Conduit | 33.33% 33.33% 33.33% | MTR. | 300.00 | 2.50 | | |
| 10. | LAMPS & FANS (i) CEILING FANS 48" (ii) 1.20 M FLUORSCENT TUBE WITH FITTINGS | 50 % 50 % | EACH | 1024.00 | 3.50 | | |
| 11. | ELECTMACHINERY FITTING MOTORS 7.5 HP (PUMP SET) 1500 RPM (KIRLOSKAR) | | EACH | 30380.00 | 2.50 | | |
| 12. | WIRES & CABLES COPPER WIRES` (a) 1.5 SQMM (b) 4.0 SQMM | 70% 30% | 100 MTR. | 1790.00 | 4.00 | | |
| 13. | LABOUR (i) SKILLED (ii) UNSKILLED | 50 % 50 % | EACH | 309.38 | 25.00 | | |